







Fitting for 2–3 bottom-running wooden doors (19/25 mm) up to 50 kg (110 lbs.) with screwed on running track. Design Mixslide without soft close


Product highlights

 **Aesthetics** Bottom-running system that supports the entire door weight on the base makes cabinet designs with thin materials possible


 **Comfort** Smooth, silent running with Hawa Comfort roller

Technical specifications

	Max.	50 kg (110 lbs.)
	Max.	2400 mm (7'10 7/16")
	Max.	1400 mm (4'7 1/8")
		19/25 mm (3/4" or 31/32")



















Installation examples



















Set for 2 or 3 wooden doors, 19 mm (3/4")

	No.
Hawa Combino 50 H MS, door thickness 19 mm (3/4"), for 2 doors	055.3199.071
Hawa Combino 50 H MS, door thickness 19 mm (3/4"), for 3 doors	055.3199.073


		055.3199.071	055.3199.073	No.
Set consisting of:				
	Running gear, interior door, steel, zinc-plated	2	4	055.3169.071
	Running gear, exterior door, 19 mm (3/4"), steel, zinc-plated	2	2	055.3113.175
	Guide bracket, steel, zinc-plated	4	6	055.3059.171
	Guide bracket housing, plastic, anthracite	4	6	055.0282.001
	Anti-derailment device, plastic, red	4	6	055.0186.001
	Stopper, plastic, gray	4	4	055.3167.071
	Retention spring for stopper, plastic, gray	2	3	055.0204.001
	Stopper guide, plastic, gray	4	4	040.3079.074
	Door follower, with 2 doors, steel, zinc-plated	1		055.3124.071
	Track end piece, plastic, gray, 31 mm (1 7/32")	3	4	040.3083.002
	Track end piece, plastic, gray, 22 mm (7/8")	1		040.3083.003
	Washer-and-screw assembly, 4.5x17 mm, steel, zinc-plated	16	24	055.0100.101
	Countersunk head screw, 4.5x20 mm, steel, zinc-plated	16	24	600.0000.167
	Countersunk head screw, 3.5x20 mm, steel, zinc-plated	4	4	766.5035.120
	Door follower, with 3 doors, 2-piece set, steel, zinc-plated		1	056.3095.171
	Buffer, with adhesive, 2-piece set		1	053.3364.051

Set for 2 or 3 wooden doors, 25 mm (31/32")


	No.
Hawa Combino 50 H MS, door thickness 25 mm (31/32"), for 2 doors	055.3199.072
Hawa Combino 50 H MS, door thickness 25 mm (31/32"), for 3 doors	055.3199.074

		055.3199.072	055.3199.074	No.
Set consisting of:				
	Running gear, interior door, steel, zinc-plated	2	4	055.3169.071
	Running gear, exterior door, 25 mm (31/32"), steel, zinc-plated	2	2	055.3114.175
	Guide bracket, steel, zinc-plated	4	6	055.3059.171
	Guide bracket housing, plastic, anthracite	4	6	055.0282.001
	Anti-derailment device, plastic, red	4	6	055.0186.001
	Stopper, plastic, gray	4	4	055.3167.071
	Retention spring for stopper, plastic, gray	2	3	055.0204.001
	Stopper guide, plastic, gray	4	4	040.3079.074
	Door follower, with 2 doors, steel, zinc-plated	1		055.3124.071
	Track end piece, plastic, gray, 31 mm (1 7/32")	3	4	040.3083.002
	Track end piece, plastic, gray, 22 mm (7/8")	1		040.3083.003
	Washer-and-screw assembly, 4.5x17 mm, steel, zinc-plated	16	24	055.0100.101
	Countersunk head screw, 4.5x25 mm, steel, zinc-plated	16	24	766.5045.125
	Countersunk head screw, 3.5x20 mm, steel, zinc-plated	4	4	766.5035.120
	Door follower, with 3 doors, 2-piece set, steel, zinc-plated		1	056.3095.171
	Buffer, with adhesive, 2-piece set		1	053.3364.051



Running tracks

	Double running track, aluminum, anodized, pre-drilled	mm (inch)	No.
		2500 (8' 2 7/16")	055.3161.250
		3500 (11' 5 25/32")	055.3161.350
		6000 (19' 8 7/32")	055.3161.600


Guide tracks

	Guide track, aluminum, pre-drilled	mm (inch)	No.
		2500 (8'2 7/16")	056.3079.250
		3500 (11'5 25/32")	056.3079.350
		6000 (19'8 7/32")	056.3079.600



Accessories

		No.
	Intermediate stop set, for 3 doors	055.3218.071
	Drilling and milling jig, for processing guide brackets, wood	055.3099.001


Handle profiles




Calculations



Track end piece



Intermediate stop with 3 doors



Accessories

- Straightening fitting from page 265
- Handle profiles from page 268

Planning/execution

Further information about the product can be found on www.hawa.com.