








Fitting for 2 telescopic opening glass doors up to 80 kg (176 lbs.), with surface mounted running track. Ceiling mounting.

Product highlights


-  **Flexibility** Door openings up to 3000 mm (9'10 1/8") wide
-  **Flexibility** Telescopic opening without guide track

Technical specifications
















-  Max. 80 kg (176 lbs.)
-  Max. 2600 mm (8'6 3/8")
-  500–1000 mm (1'7 11/16" to 3'3 3/8")
-  8–16 mm (5/16" to 5/8")
(Fully tempered monolithic glass (ESG))







Installation examples






Set for 2 glass door up to 80 kg (176 lbs.)

		No.	
Hawa Junior 80 G Telescopic, for 2 doors		25659	
		25659	No.
Set consisting of:			
	Running gear, 2-wheeled, M10, ball bearings	4	30600
	Suspension plate, with suspension bolt M10	4	14543
	Stopper Hawa Junior 80/100, with adjustable retention spring	2	30138
	Cover cap for glass suspension profile, plastic, anthracite	8	20907
	Glass holder insert, plastic, with countersunk head screw, M6x30 mm (1/4" x 1 3/16")	8	10792
	Guide pulley wheel, with fixing plate, long	1	20139
	Guide pulley wheel, with fixing plate, short	1	20140
	Driver, wide	1	20141
	Toothed belt, 2,7 m (8'10 5/16"), fibre glass reinforced, black	1	20208
	Toothed belt fixing device for ceiling/wall mounting	1	20732
	Driver counter-plate, wide	1	20246
	Suspension plate	3	21262
	Screw-on rubber door stop	1	10629
	Rattle-proof mounted guide, with wheels, complete	1	24906
	Rattle-proof mounted guide, with wheels	1	24905


Suspension and glass retaining profiles

		mm (inch)	No.
	Glass suspension/retainer profile, aluminum, anodized, brushed, glass up to 8-16 mm (5/16"-5/8")	6,500 (21' 3 29/32")	21783
	cut to size		21784
	Glass suspension/retainer profile, aluminum, glass up to 16 mm (5/8")	6,500 (21' 3 29/32")	13158
	Glass suspension/retainer profile, aluminum, glass up to 16 mm (5/18")	cut to size	13159
	Glass suspension/retainer profile, aluminum, anodized, brushed, glass up to 8-10 mm (5/16"-13/32")	6,500 (21' 3 29/32")	21781
	cut to size		21782
	Glass suspension/retainer profile, aluminum, glass up to 10 mm (13/32")	6,500 (21' 3 29/32")	10348
	cut to size		10349
	Multi purpose suspension and retainer profile, aluminum, anodized, undrilled	6,500 (21' 3 29/32")	10345
	cut to size		12915



Cover caps

		No.
	Cover cap for glass suspension/retainer profile 21783/21784/13158/13159, glass up to 16 mm (5/8"), plastic, anthracite	21085
	Cover cap for glass suspension/retainer profile 21781/21782/10348/10349, glass up to 10 mm (13/32"), plastic, anthracite	21512
	Cover cap for glass suspension profile, plastic, anthracite	20907


Glass holder
Order 2 pieces per suspension and glass retaining profile

		No.
	Glass holder insert, plastic, with countersunk head screw, M6x30 mm (1/4" x 1 3/16")	10792


Bottom guides

		No.
	Rattle-proof mounted guide, with wheels	24905
	Connecting bolt for bottom guide track, 6x40 mm (1/4"x1 9/16"), steel, zinc-plated	13759



Running tracks

		mm (inch)	No.
	Running track, aluminum, anodized, pre-drilled	1,400 (4' 7 1/8 ")	10189
		1,600 (5' 3 ")	10190
		1,800 (5' 10 7/8 ")	10191
		2,000 (6' 6 3/4 ")	10192
		2,200 (7' 2 5/8 ")	10193
		2,500 (8' 2 7/16 ")	10194
		3,000 (9' 10 1/8 ")	18532
		4,000 (13' 1 15/32 ")	18533
		6,000 (19' 8 7/32 ")	10186
		cut to size	10188








Guide tracks

		mm (inch)	No.
	Guide track, aluminum, anodized, pre-drilled	6,000 (19' 8 7/32 ")	13688
		cut to size	13690


Wall connection

		mm (inch)	No.
	Wall profile, aluminum, anodized	2,500 (8' 2 7/16")	17020
		3,500 (11' 5 25/32")	17021
	Wall profile, aluminum, stainless steel look, brushed	2,500 (8' 2 7/16")	20119
		3,500 (11' 5 25/32")	20120
	Seal profile, black, for wall profile	2,500 (8' 2 7/16")	16452
		3,500 (11' 5 25/32")	16453








Integrated locks

		No.
	Bar bolt lock for 17 mm profile cylinder (21/32"), with retention pin	16760
	Bar bolt lock for 22 mm round cylinder (7/8"), with retention pin	16761
	Bar bolt lock for square/ hexagon socket, with retention pin	16762
	Bar bolt lock for 17 mm (21/32") profile cylinder, with guide pin and fixing parts	18484
	Bar bolt lock for 22 mm (7/8") round cylinder, with guide pin and fixing parts	18485
	Bar bolt lock for square/ hexagon socket, with guide pin and fixing parts	18486
	Security rose 16 mm (5/8"), for profile cylinder 17/61 mm (21/32"/2 13/32"), chrome nickel steel	18502
	Spacer for security rose for 17 mm (21/32") profile cylinder, 10 mm (13/32") glass	18493
	Spacer for security rose for 22 mm (7/8") round cylinder, 10 mm (13/32") glass	18494
	Floor-mounted sleeve, with oblong hole and chromium- plated brass spring cover	13787
	Rosette for floor-mounted sleeve	17326
	Strike plate, steel, chrome-plated	13130


Fixed Glass

		mm (inch)	No.
	Bottom profile for stationary glass and wood element, aluminum, anodized	6,000 (19' 8 7/32")	14691
		cut to size	14692

Accessories


		No.
	Cover cap to running track, both sides, steel, chrome-plated, matt	24956
	Top-fixing plate for stationary glass, with hanger bolt M12	14687
	Bottom door stopper, with centering, stainless steel look	21473
	Bottom door stopper, with centering, chrome-plated, matt	20773
	Guide, rattle proof, with suspension block, plastic, 14 mm (9/16")	13781
	Centering assembly grey, for all glass sliding doors	18619
	Centering assembly black, for all glass sliding doors, to wall profile	18663

Calculations of door widths




Wall connection

Optimal wall connection for all-glass sliding doors with unprotected glass edge.




Integrated locks

An integrated bar bolt lock, suitable for the 17 mm (21/32") profile cylinder, 22 mm (7/8") round cylinder and a square/hexagonal socket, is available to secure the all-glass sliding doors.



Individual solution



Accessories

- Lock solutions from page 511
- General accessories from page 518
- Glass recommendations from page 536

Planning/execution

Further information about the product can be found on www.hawa.com.