


Fitting for top-running glass doors up to 100 kg (220 lbs.), with surface mounted running track. Optionally with soft and self closing mechanism. Wall or ceiling mounting. With fixed glass support profile.

Product highlights



- Comfort** Smooth, quiet sliding and gentle stopping of the door with integrated soft and self closing system
- Aesthetics** Large glass systems can be implemented as passage or room doors

Technical specifications

- Max. 100 kg (220 lbs.)
- Max. 2700 mm (8'10 5/16")
- Max. 1600 mm (5'3")
- 8-12.7 mm (5/16" to 1/2")




Installation examples




**Set for ceiling or wall mounting,
for 1 glass door up to 100 kg (220 lbs.)**

	No.
Hawa Porta 100 G/GU/GM/GF, for 1 door	057.3074.071



Set consisting of:

		057.3074.071	No.
	Running gear, ball bearing, rollers plastic white	2	057.3114.071
	Stopper, with retention spring, plastic, gray	1	057.3073.072
	Stopper, without retention spring, plastic, gray	1	057.3073.071
	Suspension bolt, M8x32 mm (5/16"x1 1/4"), steel, zinc-plated	2	057.0123.104
	Hexagon locking nut, M8, steel, zinc-plated	2	768.9005.101
	Clamping shoe, aluminum, glass thickness 8–12.7 mm (5/16"-1/2")	2	057.3032.075
	Hexagon screw, M6x20 mm, plastic, white	2	762.9480.000
	Hexagon jam nut, M6, steel, zinc-plated	2	768.2001.101
	Bottom guide, playfree adjustable, chrome-plated, matt	1	057.3030.071
	Wall buffer, 19x10 mm (3/4"x13/32"), rubber, black	1	024.0002.046
	Countersunk head screw, 4x20 mm (5/32"x25/32"), steel, zinc-plated	3	766.5042.120




Running tracks

	mm (inch)	No.
	2,500 (8'2 7/16")	057.3053.250
	3,500 (11'5 25/32")	057.3053.350
	6,000 (19'8 7/32")	057.3053.600
	cut to size	057.3053.990

Panels


		mm (inch)	No.
	Clip-on panel, aluminum, anodized	2,500 (8'2 7/16")	057.3050.250
		3,500 (11'5 25/32")	057.3050.350
		6,000 (19'8 7/32")	057.3050.600
		cut to size	057.3050.990
	Screening seal for fascias, plastic, black	20,000 (65' 7 13/32")	057.3078.002

Fixed glass support profiles

		mm (inch)	No.
	Fixed glass profil/guide track, aluminum, anodized, pre-drilled	2,500 (8'2 7/16")	057.3056.250
		3,500 (11'5 25/32")	057.3056.350
		6,000 (19'8 7/32")	057.3056.600
		cut to size	057.3056.990
	Fixed glass support profile, aluminum, anodized, pre-drilled	2,500 (8'2 7/16")	057.3057.250
		cut to size	057.3057.990
	Sealing profile for fixed glass support profile, glass thickness 8–10 mm (5/16"-13/32"), plastic, black	20,000 (65' 7 13/32")	057.3072.001


Set fixing set

	No.
Fixing set, aluminum, anodized, for fixed glass support profile 057.3057., fixed glass profil/guide track 057.3056.	057.3076.071

	057.3076.071	No.
	Cover, aluminum, anodized	2
		057.3062.001
	Thread rolling rounded head screw, M4x10 mm (5/32"x13/32"), steel, zinc-plated	15
		762.7008.100

Set consisting of:




Clip-on components

	No.
 <p>Clip component for wooden and aluminum panel, every 500 mm (1'7 11/16"), aluminium, pre-drilled</p>	057.3117.001

Panel end component set, 64.5 mm (2 9/16"), aluminum

	No.
Panel end component set, 64.5 mm (2 9/16"), one-sided, wall mounting	057.3052.072




Set consisting of:

	057.3052.072	No.
 <p>Panel end component, 64.5 mm (2 9/16"), aluminum, anodized</p>	1	057.3052.902
 <p>Bracker connector, steel, zinc-plated</p>	2	057.3051.101
 <p>Screw, M4x2.6 mm (5/32"x 1/8"), steel, zinc-plated</p>	4	011.0101.171

Panel end component set, 70.5 mm (2 25/32"), aluminum

	No.
Panel end component set, 70.5 mm (2 25/32"), one-sided, ceiling mounting	057.3052.073

Set consisting of:





	057.3052.073	No.
 <p>Panel end component, 70.5 mm (2 25/32"), aluminum, anodized</p>	1	057.3052.903
 <p>Bracker connector, steel, zinc-plated</p>	2	057.3051.101
 <p>Screw, M4x2.6 mm (5/32"x 1/8"), steel, zinc-plated</p>	4	011.0101.171

Soft close


For soft closing in opening and closing direction
order 2 sets.

	No.
Soft close Hawa Porta 100, Divido 100, 61–100 kg (133–220 lbs.), 1 piece	042.3102.071
Soft close Hawa Porta 60/100, Divido 100, 10–60 kg (22–132 lbs.), 1 piece	042.3102.072





Set consisting of:

	042.3102.071	042.3102.072	No.
 <p>Soft close, top running, 61–100 kg (133 to 220 lbs.), plastic</p>	1		042.3106.071
 <p>Trigger for soft close in buildings, zinc die casting</p>	1	1	042.3105.001
 <p>Screw set soft close</p>	1	1	600.0000.566
 <p>Soft close, top running, 10–60 kg (22 to 132 lbs.), plastic</p>		1	042.3106.072


Wall compensation profiles

	mm (inch)	No.
 <p>Wall compensation profile, with sealing profile gray, aluminum, anodized</p>	2,500 (8' 2 7/16")	042.3064.071
	3,000 (9' 10 1/8")	042.3064.072


Accessories

	No.
 <p>Bottom door stopper, with centering, chrome-plated, matt</p>	20773
 <p>Sliders, for 8 mm (5/16") glass, self-adhesive, 6-piece set</p>	16192
 <p>Sliders, for 10 mm (13/32"), self-adhesive, 6-piece set</p>	16193
 <p>Track cleaner, plastic, blue</p>	057.3099.071


Wooden panels




Calculations of panels




Bottom door stopper



U-shaped guide track with sliders



Soft close



Accessories

- Lock solutions from page 511
- General accessories from page 518
- Glass recommendations from page 536

Planning/execution

Further information about the product can be found on www.hawa.com.