


Fitting for 2 synchronously opening glass doors up to 100 kg (220 lbs.), with surface mounted running track or running track flush with the ceiling. Ceiling mounting.

Product highlights







- Flexibility** Standard applications can be extended with the Synchro option
- Comfort** Two simultaneously sliding doors make large, fully accessible openings possible
- Aesthetics** Also available in black as a "Black Edition" design option for a particularly attractive appearance

Technical specifications

- Max. 100 kg (220 lbs.)
- Max. 2700 mm (8'10 5/16")
- Max. 1200 mm (3'11 1/4")
- 8–12.7 mm (5/16" to 1/2")
















Installation examples



**Set for ceiling or wall mounting, for 1 glass door
up to 100 kg (220 lbs.)**







	No.
Hawa Porta 100 GW, for 1 door	057.3091.071
Hawa Porta 100 GWF, black, for 1 door	057.3091.075

Set consisting of:




		057.3091.071	057.3091.075	No.
	Running gear, ball bearing, rollers plastic white	2	2	057.3114.071
	Stopper, with retention spring, plastic, gray	1		057.3073.072
	Stopper, without retention spring, plastic, gray	1		057.3073.071
	Suspension bolt, M8x25 mm, flat head, steel, black	2	2	600.0000.473
	Clamping shoe, glass thickness 6-12.7 mm (1/4"-1/2"), aluminum	2	2	057.3087.071
	Bottom guide, playfree adjustable, glass thickness 8-12.7 mm (5/16"-1/2"), chrome-plated, mat	1		057.3082.071
	Wall buffer, 19x10 mm (3/4"x13/32"), rubber, black	1	1	024.0002.046
	Clip for panel, every 300 mm (11 13/16"), plastic, gray, 12-piece set	1	1	057.3086.051
	Countersunk head screw, 4x20 mm (5/32"x25/32"), steel, zinc-plated	3		766.5042.120
	Stopper, with retention spring, plastic, black		1	057.3073.076
	Stopper, without retention spring, plastic, black		1	057.3073.075
	Bottom guide, playfree adjustable, black		1	057.3082.075
	Countersunk head screw, 4x20 mm, steel, zinc-plated		3	600.0000.817

Synchro set


	No.
Hawa Porta 100 GW/GWF Synchro	057.3092.071

		mm (inch)	057.3092.071	No.
	Cable holder, right, steel, zinc-plated		1	057.3088.171
	Cable holder, left, steel, zinc-plated		1	057.3088.172
	Deviating roller		2	057.3090.171
	Kevlar cable, D= 2.5 mm (3/32")	10,000 (32' 9 11/16")	1	752.0059.104
	Protectiv edge trim, plastic, black	2,700 (8'10 5/16")	1	057.3080.001
	Head cap screw, M5x8 mm (3/16"x5/16"), steel, zinc-plated		2	600.0000.171




Running tracks

		mm (inch)	No.
	Running track, aluminum, anodized, pre-drilled	2,500 (8' 2 7/16")	057.3084.250
		3,500 (11' 5 25/32")	057.3084.350
		6,000 (19' 8 7/32")	057.3084.600
		cut to size	057.3084.990
	Running track, aluminum, black anodized, pre-drilled	2,500 (8' 2 7/16")	057.3084.255
		3,500 (11' 5 25/32")	057.3084.355
	Disposable cover Hawa Porta 100 GW/ GWF, plastic, black	2,000 (6' 6 3/4 ")	057.3089.001
		cut to size	057.3089.990




Front edge profiles

		mm (inch)	No.
	Front edge profile for 057.3084./042.3001./042.3038., aluminum, anodized	2,500 (8' 2 7/16")	042.3005.250
		3,000 (9' 10 1/8 ")	042.3005.300
		6,000 (19' 8 7/32")	042.3005.600
		cut to size	042.3005.990
	Front edge profile for 057.3084., aluminum, black anodized	2,500 (8' 2 7/16")	042.3005.255

Panels




		mm (inch)	No.
	Panel profile, aluminum, anodized	2,500 (8' 2 7/16")	057.3085.250
		3,500 (11' 5 25/32")	057.3085.350
		6,000 (19' 8 7/32")	057.3085.600
		cut to size	057.3085.990
	Panel profile, aluminum, black anodized	2,500 (8' 2 7/16")	057.3085.255
		3,500 (11' 5 25/32")	057.3085.355
	Screening seal for fascias, plastic, black	20,000 (65' 7 13/32")	057.3078.002

Fixed glass support profiles





		mm (inch)	No.
	Fixed glass profil/guide track, aluminum, anodized, pre-drilled	2,500 (8' 2 7/16")	057.3056.250
		3,500 (11' 5 25/32")	057.3056.350
		6,000 (19' 8 7/32")	057.3056.600
		cut to size	057.3056.990
	Fixed glass profil/guide track, aluminum, black anodized, pre-drilled	2,500 (8' 2 7/16")	057.3056.255
		3,500 (11' 5 25/32")	057.3056.355
	Sealing profile for fixed glass support profile, glass thickness 8-10 mm (5/16"-13/32"), plastic, black	20,000 (65' 7 13/32")	057.3072.001

Set fixing set


	No.
Fixing set, aluminum, anodized, for fixed glass support profile 057.3057., fixed glass profil/guide track 057.3056.	057.3076.071
Fixing set, aluminum, black anodized, for fixed glass profil/guide track 057.3056.	057.3076.075

	057.3076.071	057.3076.075	No.
Set consisting of:			
	Cover, aluminum, anodized	2	057.3062.001
	Thread rolling rounded head screw, M4x10 mm (5/32"x13/32"), steel, zinc-plated	15	762.7008.100
	Cover, aluminum, anodized black	2	057.3062.005


Accessories

	No.
	20773
	057.3094.001
	600.0000.309
	057.3099.071


Ceiling integration



Bottom door stopper



Calculations



Accessories

- Lock solutions from page 511
- General accessories from page 518
- Glass recommendations from page 536

Planning/execution

Further information about the product can be found on www.hawa.com.