

**Fitting for top-running wooden doors up to 40 kg (88 lbs.), with screwed on running track.
Design Inside. Fully opening.**

Product-Highlights



Flexibility

Curved tracks with a radius of more than 2000 mm (6' 6 3/4'') allow for unusual floor plans



Aesthetics

Flush-fitting front panel with a uniform gap pattern

Technical guidelines

Door weight limit	Max.
Door height limit	Max.
Door width limit	Max.
Door weight	40 kg (88 lbs.)
Door thickness	19–25 mm (3/4" to 31/32")
Door height	2600 mm (8' 6 3/8")
Door width	900 mm (2' 11 7/16")

Application area

Utilization light / semi-public access	Yes
Utilization medium / semi-public access	Yes
Utilization high / public access	Yes

Warranty

With the exception of parts subject to wear and tear, Hawa warrants the flawless functioning of the products delivered by it, as well as the durability of all parts, for a period of 2 years commencing from the transfer of risk.

Product Design

Hawa Aperto 40 F IS consisting of running track incl. curve for parking area (aluminum wall thickness 2.8 mm (1/8'')) 2-piece, suspension brackets, running gear with ball bearing rollers, fixing cup with hanger bolt, spacers for door gaps, end buffer, bottom guide pin, bottom guide profile

Optional:

- (...) Center stop
- (...) Straightening fitting

Interfaces

Door leaf

- Top, drill hole at rear for suspension
- Suspension cup with screw fixing
- Door thickness 19–25 mm (3/4" to 31/32")
- Bottom guide part, screwed on at rear

Parking area

- Up to 7 sliding door elements