

Fitting for top-running wooden doors up to 60 kg (132 lbs.), with surface mounted running track. Ceiling mounting. Fully opening.

Product-Highlights



Aesthetics

Specially developed for light partition walls up to 60 kg (132 lbs.), allowing for visible parts with smaller dimensions



Productivity

Order the entire system with three to four article numbers

Technical guidelines

Max. Door weight	60 kg (132 lbs.)
Door thickness	35–50 mm (1 3/8" to 1 31/32")
Max. Door height	2600 mm (8' 6 3/8")
Max. Door width	1500 mm (4' 11 1/16")
Max. Opening width	13600 mm (44' 7 7/16")
Height adjustable	+/- 3 mm (1/8")
Soft close	No
Door material	Wood
Finish color of visible profiles	Aluminum anodized

System options

Ceiling mounting	Yes
Top-running	Yes

Application area

Utilization light / semi-public access	Yes
Utilization medium / semi-public access	Yes
Utilization high / public access	Yes

Warranty

With the exception of parts subject to wear and tear, Hawa warrants the flawless functioning of the products delivered by it, as well as the durability of all parts, for a period of 2 years commencing from the transfer of risk.

Product Design

Hawa Aperto 60 H consisting of running track incl. curve for parking area (aluminum wall thickness 2.8 mm (1/8")) 2-piece, suspension brackets, running gear with ball bearing rollers, suspension profile with suspension carriage,

- Optional:
- (...) Sealing profile
 - (...) Protective edge trim
 - (...) Bottom guide
 - (...) Bottom guide profile
 - (...) Bar bolt lock
 - (...) Rotary handle

Interfaces

Door leaf

- Recess for suspension profile (H × W) 25 × 20 mm (31/32" x 25/32")
- Screwed-on suspension profiles
- Recess for bottom guide part (H × W) 25 × 20 mm (31/32" x 25/32") (optional)

Parking area

- Parking area parallel to sliding axis or at 90° to sliding axis
- Concealed parking area behind hinged door or visibly parked cabinet fronts as a design element
- An additional hinged door set must be ordered with concealed parking area behind a hinged door