

Fitting for top-running glass doors up to 40 kg (88 lbs.), with surface mounted running track. With soft and self closing mechanism. Wall mounting. Niche solution.

Product-Highlights

Productivity

Simple connection technology between the individual components makes quick installation possible


Flexibility

Different fixing methods make applications with wall-wall, glass-wall, or glass-glass combinations possible

Technical guidelines

Max. Door weight	40 kg (88 lbs.)
Door thickness	8/10 mm (5/16" to 13/32")
Max. Door height	2200 mm (7' 2 5/8")
Max. Door width	800 mm (2' 7 15/32")
Max. Opening width	1500 mm (4' 11 1/16")
Height adjustable	+2 / -3 mm (+3/32" / -1/8")
Soft close	Yes
Door material	Glass

System options

Wall mounting	Yes
Top-running	Yes

Application area

Utilization light / semi-public access	Yes
Utilization medium / semi-public access	Yes
Utilization high / public access	Yes

Tests Building hardware – Hardware for sliding doors and folding doors according to DIN EN 1527
– Duration of functionality: Class 6 (highest class = 100,000 cycles)

Hardware for furniture – Roller fittings for sliding doors according to DIN 68859
– Stop reliability
– Retention reliability

Warranty With the exception of parts subject to wear and tear, Hawa warrants the flawless functioning of the products delivered by it, as well as the durability of all parts, for a period of 2 years commencing from the transfer of risk.

Product Design

Hawa Banio 40 GF consisting of running track (aluminum), clip-on panel, running gear with friction bearing rollers, damper, stopper, clamping shoe with hanger bolt, bottom guide, handle set, splash quard profile, Banio sealing set

Optional:
(...) partial threshold

Interfaces

Door leaf

- No recess
- Clamped glass fixing

Glass wall

- Glass cut-out for corner connector