

**Fitting for top-running glass doors up to 40 kg (88 lbs.), with surface mounted running track. With soft and self closing mechanism. Glass panel installation.**

**Product-Highlights**

**Aesthetics**

A small corner element in a fitting look inserts into the filigree design and makes ceiling supports redundant


**Productivity**

Easy and quick installation thanks to the well-tried clamping shoe technology without glass processing

**Technical guidelines**

Max. Door weight	40 kg (88 lbs.)
Door thickness	8–9 mm (5/16" to 11/32")
Max. Door height	2200 mm (7' 2 5/8")
Max. Door width	800 mm (2' 7 15/32")
Max. Opening width	1500 mm (4' 11 1/16")
Height adjustable	+2 / -3 mm (+3/32" / -1/8")
Soft close	Yes
Door material	Glass

**System options**

Wall mounting	Yes
Top-running	Yes

**Application area**

Utilization light / semi-public access	Yes
Utilization medium / semi-public access	Yes
Utilization high / public access	Yes

**Tests** Building hardware – Hardware for sliding doors and folding doors according to DIN EN 1527  
– Duration of functionality: Class 6 (highest class = 100,000 cycles)

Hardware for furniture – Roller fittings for sliding doors according to DIN 68859  
– Stop reliability  
– Retention reliability

**Warranty** With the exception of parts subject to wear and tear, Hawa warrants the flawless functioning of the products delivered by it, as well as the durability of all parts, for a period of 2 years commencing from the transfer of risk.

**Product Design**

Hawa Banio 40 GF Glass panel installation consisting of running track (aluminum), glass wall mounting set, clip-on panel, running gear with friction bearing rollers, damper, stopper, clamping shoe with hanger bolt, bottom guide, handle set, splash guard profile, Banio sealing set

Optional:  
(...) partial threshold

**Interfaces**

**Door leaf**

- No recess
- Clamped glass fixing

Glass wall

- Glass cut-out for corner connector