

Fitting for top-running wooden doors up to 100 kg (220 lbs.), with surface mounted running track. With soft and self closing mechanism. Wall or ceiling mounting.

Product-Highlights

Flexibility

Ceiling mounting with integrated clip-on panel in aluminum or wood


Productivity

Multi-track guide and running tracks reduce installation cost

Technical guidelines

Max. Door weight	100 kg (220 lbs.)
Door thickness	28–30 mm (1 3/32" to 1 3/16")
Max. Door height	2400 mm (7' 10 7/16")
Max. Door width	1200 mm (3' 11 1/4")
Max. Opening width	6000 mm (19' 8 7/32")
Height adjustable	+/- 3 mm (1/8")
Soft close	Yes
Door material	Wood
Finish color of visible profiles	Aluminum anodized

System options

Wall mounting	Yes
Ceiling mounting	Yes
Top-running	Yes

Application area

Utilization light / semi-public access	Yes
Utilization medium / semi-public access	Yes
Utilization high / public access	Yes

Tests

Building hardware – Hardware for sliding doors and folding doors according to EN 1527 / 1998
 – Duration of functionality: Class 6 (highest class = 100,000 cycles)

Hardware for furniture – Roller fittings for sliding doors according to DIN 68859
 – Overload test
 – Function test

Warranty

With the exception of parts subject to wear and tear, Hawa warrants the flawless functioning of the products delivered by it, as well as the durability of all parts, for a period of 2 years commencing from the transfer of risk.

Product Design

Hawa Divido 100 H consisting of running track (aluminum), clip-on panel, running gear with ball bearing rollers, support flange, stopper with retention spring, bottom guide.

Optional:

- (...) Multi-track running track
- (...) Intermediate panel
- (...) Clip-on component for wooden and aluminum panel
- (...) Hawa Porta 100 soft and self closing mechanism
- (...) Cover cap for assembly opening
- (...) Bottom guide set for wall mounting with roller
- (...) Wall compensation profile

Interfaces

Door leaf

- Screw fixed support flange
- Guide groove (H x W) 30 x 13 mm (1 3/16" x 1/2")