

Fitting for bottom-running glass doors up to 80 kg (176 lbs.), with surface or recess mounted running track. With soft and self closing mechanism.

Product-Highlights



Flexibility

One, two or three track system can be implemented for doors or room dividers



Comfort

Smooth and quiet sliding, braking and closing of doors with soft and self closing system

Technical guidelines

Max. Door weight	80 kg (176 lbs.)
Door thickness	30 mm (1 3/16") (5.9–10 mm (7/32" to 13/32"))
Max. Door height	2750 mm (9' 9/32")
Max. Door width	2000 mm (6' 6 3/4")
Max. Opening width	6000 mm (19' 8 7/32")
Height adjustable	+/- 3 mm (1/8")
Soft close	Yes
Door material	Alu Glass Wood Mix
Finish color of visible profiles	Aluminum anodized

System options

Bottom-running	Yes
----------------	-----

Application area

Utilization light / semi-public access	Yes
Utilization medium / semi-public access	Yes
Utilization high / public access	Yes

Tests

Building hardware – Hardware for sliding doors and folding doors according to EN 1527 / 1998
– Duration of functionality: Class 6 (highest class = 100,000 cycles)

Hardware for furniture – Roller fittings for sliding doors according to DIN 68859
– Overload test
– Function test

Warranty

With the exception of parts subject to wear and tear, Hawa warrants the flawless functioning of the products delivered by it, as well as the durability of all parts, for a period of 2 years commencing from the transfer of risk.

Product Design

Hawa Divido 80 GR consisting of bottom running track (aluminum), top guide track, running gear with ball bearing rollers and bottom running gear support, top guide set, aluminum glass frame profile, stopper.

Optional:

- (...) Multi-track bottom running track
- (...) Multi-track top guide track
- (...) Frame bars
- (...) Frame profile with vertical handle
- (...) Soft closing mechanism
- (...) Door with sloping ceiling, guided at top DS2
- (...) Door with sloping ceiling, guided at shelf DS3
- (...) Door with sloping ceiling, tapered, guided at shelf DS4
- (...) Wall compensation profile

Interfaces

Door leaf

- Profiles cut at right angles and screw fixed
- Drill hole at bottom for housing attachment