

**Fitting for bottom-running wooden doors up to 80 kg (176 lbs.), with surface or recess mounted running track. With soft and self closing mechanism.**

**Product-Highlights**

**Flexibility**

One, two or three track system for doors or room dividers


**Productivity**

Multi-track guide and running tracks reduce installation cost

**Technical guidelines**

Max. Door weight	80 kg (176 lbs.)
Door thickness	28–30 mm (1 3/32" to 1 3/16")
Max. Door height	2400 mm (7' 10 7/16")
Max. Door width	2000 mm (6' 6 3/4")
Max. Opening width	6000 mm (19' 8 7/32")
Height adjustable	+/- 3 mm (1/8")
Soft close	Yes
Door material	Wood
Finish color of visible profiles	Aluminum anodized

**System options**

Bottom-running	Yes
----------------	-----

**Application area**

Utilization light / semi-public access	Yes
Utilization medium / semi-public access	Yes
Utilization high / public access	Yes

**Tests**

Building hardware – Hardware for sliding doors and folding doors according to EN 1527 / 1998  
 – Duration of functionality: Class 6 (highest class = 100,000 cycles)

Hardware for furniture – Roller fittings for sliding doors according to DIN 68859  
 – Overload test  
 – Function test

**Warranty**

With the exception of parts subject to wear and tear, Hawa warrants the flawless functioning of the products delivered by it, as well as the durability of all parts, for a period of 2 years commencing from the transfer of risk.

### **Product Design**

Hawa Divido 80 H consisting of bottom running track (aluminum), top guide track, running gear with ball bearing rollers and bottom running gear support, top guide set, stopper.

Optional:

- (...) Multi-track bottom running track
- (...) Multi-track top guide track
- (...) Soft closing mechanism
- (...) Door with sloping ceiling, guided at top DS2
- (...) Door with sloping ceiling, guided at shelf DS3
- (...) Door with sloping ceiling, tapered, guided at shelf DS4
- (...) Wall compensation profile

### **Interfaces**

#### **Door leaf**

- Cut-out for housing at bottom (H × W × L) 40 × 18 × min. 90 mm  
(1 9/16" × 23/32" × min. 3 17/32")
- Screw fixed attachment of running gear support at bottom
- Screw fixed guide holder at top