

Fitting for pivoting, folding, and lateral sliding in of wooden doors up to 25 kg (55 lbs.) per door. Enables multi-functional room design, paired with a flush-fitting design.

Product-Highlights	Comfort	The entire furniture front can	be folded and slid in easily with one hand
	Aesthetics	Supports trends in modern ir floor-to-ceiling and accessib	nterior design towards flush-fitting, le solutions
Technical guidelines	Max. Door weight Door thickness Door height Door width Height adjustable Soft close Door material Finish color of visible	e profiles	25 kg (55 lbs.) 19–26 mm (3/4'' to 1 1/32'') 1250–2600 mm (4' 1 7/32'' to 8' 6 3/8'') 300–700 mm (11 13/16'' to 2' 3 9/16'') +/- 3 mm (1/8'') Yes Wood Aluminum anodized / aluminum black anodized
Application area	Utilization light / semi-public access Utilization medium / semi-public access		Yes Yes
Tests	Hardware for furniture – Strength and durability of slide fittings for sliding doors and roll fronts according to EN 15706 / 2009 Hardware for furniture – Strength and durability of hinges and their components - Hinges with vertical axis of rotation according to EN 15570 / 2008		
Warranty	With the exception of parts subject to wear and tear, Hawa warrants the flawless functioning of the products delivered by it, as well as the durability of all parts, for a period of 2 years commencing from the transfer of risk.		





Product Design	Hawa Folding Concepta 25 consisting of guide profiles (aluminum), scissor (steel, zinc-plated) incl. running and guide rollers, carcase connecting profiles (Connector 110 mm (4 11/32''), horizontal bar profile, cup hinges with damping, concealed centre hinges.
	Optional: () Base profile

- (....) Reinforcement profile
- (....) Locking block for espagnolette lock
- (....) Running track connection plate
- (....) Magnetic centering part
- (....) Center joint cover
- (....) Straightening fitting

Interfaces

Door leaf

- Drill holes 35 mm (1 3/8") for cup hinges
- Drill holes 35 mm (1 3/8") for centre concealed hinges
- Drill holes for fittings

Carcase side and outside

- Drill holes for fittings

Carcase construction

- Door inset
- Door hitting the floor and the upper floor
- Door in wall niche
- Door with furniture base
- Door without furniture base
- Door from worktop hitting top floor