



Fitting for top-running wooden doors up to 100 kg (220 lbs.), with surface mounted running track. Sound attenuation. Wall mounting. Minimal installation height.

Product-Highlights  **Comfort** Outstanding living comfort thanks to effective exclusion of sound, drafts, odors and unwanted light incidence

 **Flexibility** Running tracks for wall mounting with integrated clip-on system

Technical guidelines	Max. Door weight	100 kg (220 lbs.)
	Door thickness	44–50 mm (1 23/32" to 1 31/32")
	Max. Door height	2500 mm (8' 2 7/16")
	Door width	800–1430 mm (2' 7 1/2" to 4' 8 5/16")
	Opening width (LMB)	750–1250 mm (2' 5 17/32" to 4' 1 7/32")
	Height adjustable	+/- 2 mm (3/32")
	Soft close	No
	Door material	Wood
	Finish color of visible profiles	Aluminum anodized

System options	Wall mounting	Yes
	Top-running	Yes

Application area	Utilization light / semi-public access	Yes
	Utilization medium / semi-public access	Yes
	Utilization high / public access	Yes

Tests Building hardware – Hardware for sliding doors and folding doors according to EN 1527 / 2020 – Duration of functionality: Class 6 (highest class = 100,000 cycles)

Warranty With the exception of parts subject to wear and tear, Hawa warrants the flawless functioning of the products delivered by it, as well as the durability of all parts, for a period of 2 years commencing from the transfer of risk.

Product Design Hawa Junior 100 B Acoustics consisting of running track (aluminum wall thickness 2.9 mm (1/8")), running gear with ball bearing rollers (200'000 cycles tested), SoftStop, suspension profile with suspension carriage, horizontal seal set, vertical seal

Optional:
 (...) Clip-on panelling for running tracks
 (...) Panel end component, aluminum

Interfaces

Door leaf

- Suspension profile and sealing groove, top (H × W) 30 × 31 mm (1 3/16" × 1 7/32")
- Guide and sealing groove, bottom (H × W) 30 × 23 mm (1 3/16" × 29/32")
- Screw fixing of the suspension profiles and horizontal seals
- Groove for seal, vertical 4 × 4 mm (5/32" × 5/32")

Vertical seal level

- Leading surface for vertical seal must be provided by the customer (min. 6 mm (1/4") distance from wall structure)

Gap size to floor

- Air gaps of 8–12 mm (5/16" to 15/32") can be taken up by the seal