

**Fitting for top-running wooden doors up to 100 kg (220 lbs.), with surface mounted running track or running track flush with the ceiling. Sound attenuation. Ceiling mounting. Wall pocket solution.**

**Product-Highlights**



**Comfort**

Outstanding living comfort thanks to effective exclusion of sound, drafts, odors and unwanted light incidence



**Productivity**

Easy height adjustment via both suspensions and convenient depth adjustment of the installed door in the wall pocket

**Technical guidelines**

Max. Door weight	100 kg (220 lbs.)
Door thickness	44–50 mm (1 23/32" to 1 31/32")
Max. Door height	2500 mm (8' 2 7/16")
Door width	800–1300 mm (2' 7 1/2" to 4' 3 3/16")
Opening width (LMB)	750–1250 mm (2' 5 17/32" to 4' 1 7/32")
Height adjustable	+/- 2 mm (3/32")
Soft close	No
Door material	Wood
Finish color of visible profiles	Aluminum anodized

**System options**

Ceiling mounting	Yes
Ceiling mounting recessed	Yes
Top-running	Yes

**Application area**

Utilization light / semi-public access	Yes
Utilization medium / semi-public access	Yes
Utilization high / public access	Yes

**Tests** Building hardware – Hardware for sliding doors and folding doors according to EN 1527 / 2020 – Duration of functionality: Class 6 (highest class = 100,000 cycles)

**Warranty** With the exception of parts subject to wear and tear, Hawa warrants the flawless functioning of the products delivered by it, as well as the durability of all parts, for a period of 2 years commencing from the transfer of risk.

**Product Design** Hawa Junior 100 B Pocket Acoustics consisting of running track (aluminum wall thickness 2.9 mm (1/8")), running gear with ball bearing rollers (200'000 cycles tested), SoftStop, suspension profile with suspension carriage, horizontal seal set, vertical seal

Optional:  
 (...) Set for installable and removable running track  
 (...) Top track fastening for removable top track  
 (...) Spring loaded buffer

## Interfaces

### Door leaf

- Suspension profile and sealing groove, top (H × W) 30 × 31 mm (1 3/16" × 1 7/32")
- Guide and sealing groove, bottom (H × W) 30 × 23 mm (1 3/16" × 29/32")
- Screw fixing of the suspension profiles and horizontal seals
- Groove for seal, vertical 4 × 4 mm (5/32" × 5/32")

### Vertical seal level

- Leading surface for vertical seal must be provided by the customer (min. 6 mm (1/4") distance from wall structure)

### Gap size to floor

- Air gaps of 8–12 mm (5/16" to 15/32") can be taken up by the seal

### Pocket construction

- Pocket construction must be taken care of by the customer

### Assembly set

- The retainer profile is installed during the creation of the pocket construction