

Fitting for top-running glass doors up to 100 kg (220 lbs.), with surface mounted running track or running track flush with the ceiling. Optionally with soft and self closing mechanism. Ceiling mounting. Minimal installation height. Wall pocket solution.

Product-Highlights

Comfort

Accessible opening and soft and self closing at both sides from door widths of 800 mm (2' 7 1/2")


Productivity

Door can be installed in pocket after construction is complete


Security

Performance guarantee: 15 years for private use and 7 years for commercial use on incomparably low opening forces of max. 22 N

Technical guidelines

| | |
|--|---|
| Max. Door weight | 100 kg (220 lbs.) |
| Door thickness | 8–12.7 mm (5/16" to 1/2") |
| Max. Door height | 4000 mm (13' 1 15/32") |
| Max. Door width | 1500 mm (4' 11 1/16") |
| Max. Opening width | 1465 mm (4' 9 11/16") |
| Height adjustable | +/- 3 mm (1/8") |
| Soft close | Yes |
| Guaranteed opening force with damping* | Max. 22 N (fully accessible) |
| Door material | Glass |
| Finish color of visible profiles | Aluminum anodized / aluminum stainless steel effect |

System options

| | |
|---------------------------|-----|
| Ceiling mounting | Yes |
| Ceiling mounting recessed | Yes |
| Top-running | Yes |

Application area

| | |
|---|-----|
| Utilization light / semi-public access | Yes |
| Utilization medium / semi-public access | Yes |
| Utilization high / public access | Yes |

Tests Building hardware – Hardware for sliding doors and folding doors according to EN 1527 / 2013
 – Duration of functionality: Class 6 (highest class = 100,000 cycles)

*see warranty

Warranty

Performance guarantee for all official Hawa Junior 100 versions with magnetic soft close system: Guaranteed opening force of the sliding doors of max. 22 N for 15 years in domestic use and 7 years in commercial use

The performance guarantee is valid worldwide with the exception of contractual partners with their registered office/residence in the USA and use of the products by end users with registered office/residence in the USA.

Additional function guarantee on all parts other than those subject to wear and tear: 2 years

Product Design

Hawa Junior 100 GP Pocket consisting of running track (aluminum wall thickness 2.9 mm (1/8")), running gear with friction bearing rollers, stopper, spring buffer or soft closing mechanism Hawa SoftMove 100, Glass suspension with point fixing, bottom guide with zero clearance

Optional:

(...) Set for installable and removable running track, aluminum

Interfaces

Door leaf

- Glass processing for glass holders
- Positive-fit glass fixing with point fixing

Assembly set

- The retainer profile is installed during the creation of the pocket construction

Pocket construction

- Pocket construction must be taken care of by the customer