

Fitting for top-running wooden doors up to 120 kg (264 lbs.), with surface mounted running track. Optionally with soft and self closing mechanism. Wall or ceiling mounting.

Product-Highlights

Comfort

High quality, long-lasting friction bearing for quiet, smooth running, even with heavier weights


Flexibility

Steel suspension bracket for screw fixing or welding

Technical guidelines

Max. Door weight	120 kg (264 lbs.)
Door thickness	35–80 mm (1 3/8" to 3 5/32")
Max. Door height	4000 mm (13' 1 15/32")
Max. Door width	3000 mm (9' 10 1/8")
Max. Opening width	2950 mm (9' 8 5/32")
Height adjustable	+/- 3 mm (1/8")
Soft close	Yes
Door material	Wood
Finish color of visible profiles	Aluminum anodized

System options

Wall mounting	Yes
Ceiling mounting	Yes
Top-running	Yes

Application area

Utilization light / semi-public access	Yes
Utilization medium / semi-public access	Yes
Utilization high / public access	Yes

Tests Building hardware – Hardware for sliding doors and folding doors according to EN 1527 / 2013 – Duration of functionality: Class 6 (highest class = 100,000 cycles)

Hardware for furniture – Strength and durability of slide fittings for sliding doors and roll fronts according EN 15706 / 2009

Warranty With the exception of parts subject to wear and tear, Hawa warrants the flawless functioning of the products delivered by it, as well as the durability of all parts, for a period of 2 years commencing from the transfer of risk.

Product Design

Hawa Junior 120 A consisting of running track (aluminum wall thickness 3.8 mm (5/32")), running gear with friction bearing rollers, stopper or soft closing mechanism Hawa SoftMove 120, suspension profile with suspension carriage, bottom guide with zero clearance

Optional:

- (...) Guide track, for groove mounting, plastic
- (...) Fixing component Hawa SoundEx
- (...) Bottom door stopper, with centering part
- (...) Wall bottom guide Hawa Confort 120

Interfaces

Door leaf

- Screw fixed or welded attachment of the support flange
- Guide groove (H × B) 20 × 10 mm (25/32" × 13/32") (20 × 12 mm (25/32" × 15/32") with plastic guide track)