

Fitting for top-running glass doors up to 120 kg (264 lbs.), with surface mounted running track or running track flush with the ceiling. Optionally with soft and self closing mechanism. Wall or ceiling mounting.

Product-Highlights



Aesthetics

Neutral, linear design



Security

Very safe thanks to positive-fit glass fixing

Technical guidelines

Max. Door weight	120 kg (264 lbs.)
Door thickness	8–16 mm (5/16" to 5/8")
Max. Door height	4000 mm (13' 1 15/32")
Max. Door width	3000 mm (9' 10 1/8")
Max. Opening width	2950 mm (9' 8 5/32")
Height adjustable	+/- 3 mm (1/8")
Soft close	Yes
Door material	Glass

System options

Wall mounting	Yes
Ceiling mounting	Yes
Ceiling mounting recessed	Yes
Top-running	Yes

Application area

Utilization light / semi-public access	Yes
Utilization medium / semi-public access	Yes
Utilization high / public access	Yes

Tests Building hardware – Hardware for sliding doors and folding doors according to EN 1527 / 2013
– Duration of functionality: Class 6 (highest class = 100,000 cycles)

Hardware for furniture – Strength and durability of slide fittings for sliding doors and roll fronts according to EN 15706 / 2009

Warranty With the exception of parts subject to wear and tear, Hawa warrants the flawless functioning of the products delivered by it, as well as the durability of all parts, for a period of 2 years commencing from the transfer of risk.

Product Design

Hawa Junior 120 G consisting of running track (aluminum wall thickness 3.5 mm (5/32")), running gear with friction bearing rollers, stopper or soft closing mechanism Hawa SoftMove 120, suspension profile with suspension carriage, bottom guide with zero clearance, suspension and glass retaining profiles

Optional:

- (...) Guide track
- (...) Running track set with fixed glazing
- (...) Angled profile for wall mounting
- (...) Cover cap to angled profile
- (...) Hawa Adapto concrete casting system 120
- (...) Bar bolt lock
- (...) Bottom door stopper, with centering part

Interfaces

Door leaf

- Glass processing for glass holders
- Positive-fit glass fixing on suspension and glass retaining profiles

Hawa Adapto concrete casting system

- The Hawa Adapto 120 concrete casting system is already integrated in the concrete ceiling of the building shell