

Fitting for top-running glass doors up to 120 kg (264 lbs.), with surface mounted running track or running track flush with the ceiling. Optionally with soft and self closing mechanism. Wall or ceiling mounting. Minimal installation height.

Product-Highlights	Aesthetics Cover caps in different des	Cover caps in different design versions	
	Productivity Easy height adjustment via door	Easy height adjustment via both suspensions on completely installed door	
Technical guidelines	Max. Door weight	120 kg (264 lbs.)	
	Door thickness	8–12.7 mm (5/16'' to 1/2'')	
	Max. Door height	4000 mm (13' 1 15/32'')	
	Max. Door width	3000 mm (9' 10 1/8'')	
	Max. Opening width	2950 mm (9' 8 5/32'')	
	Height adjustable	+/- 3 mm (1/8'')	
	Soft close	Yes	
	Door material	Glass	
System options	Wall mounting	Yes	
	Ceiling mounting	Yes	
	Ceiling mounting recessed	Yes	
	Top-running	Yes	
A 11 11		X	
Application area	Utilization light / semi-public access	Yes	
	Utilization medium / semi-public access	Yes	
	Utilization high / public access	res	
Tests	 Building hardware – Hardware for sliding doors and folding doors according to EN 1527 / 2013 – Duration of functionality: Class 6 (highest class = 100,000 cycles) Hardware for furniture – Strength and durability of slide fittings for sliding doors and roll fronts according to EN 15706 / 2009 		
Warranty		th the exception of parts subject to wear and tear, Hawa warrants the flawless nctioning of the products delivered by it, as well as the durability of all parts, for a period 2 years commencing from the transfer of risk.	





Product Design

Hawa Junior 120 GP Pocket consisting of running track (aluminum wall thickness 3.5 mm (5/32'')), running gear with friction bearing rollers, stopper, spring buffer or soft closing mechanism Hawa SoftMove 120, Glass suspension with point fixing, bottom guide with zero clearance

Optional:

- (....) Guide tracks
- (....)Track set for fixed glazing
- (....) Concrete casting system Hawa Adapto 120
- (....) Bottom door stopper, with centering part

Interfaces

Door leaf

- Glass processing for glass holders
- Positive-fit glass fixing with point fixing

Hawa Adapto concrete casting system

- The Hawa Adapto 80 concrete casting system is already integrated in the concrete ceiling of the building shell