

Fitting for top-running glass doors up to 120 kg (264 lbs.), with surface mounted running track or running track flush with the ceiling. Optionally with soft and self closing mechanism. Ceiling mounting. Minimal installation height. Wall pocket solution.

Product-Highlights

Aesthetics

Cover caps in different design versions


Productivity

Easy height adjustment via both suspensions on completely installed door

Technical guidelines

Max. Door weight	120 kg (264 lbs.)
Door thickness	8–12.7 mm (5/16" to 1/2")
Max. Door height	4000 mm (13' 1 15/32")
Max. Door width	1500 mm (4' 11 1/16")
Max. Opening width	1470 mm (4' 9 7/8")
Height adjustable	+/- 3 mm (1/8")
Soft close	Yes
Door material	Glass

System options

Ceiling mounting	Yes
Ceiling mounting recessed	Yes
Top-running	Yes

Application area

Utilization light / semi-public access	Yes
Utilization medium / semi-public access	Yes
Utilization high / public access	Yes

Tests Building hardware – Hardware for sliding doors and folding doors according to EN 1527 / 2013 – Duration of functionality: Class 6 (highest class = 100,000 cycles)

Hardware for furniture – Strength and durability of slide fittings for sliding doors and roll fronts according to EN 15706 / 2009

Warranty With the exception of parts subject to wear and tear, Hawa warrants the flawless functioning of the products delivered by it, as well as the durability of all parts, for a period of 2 years commencing from the transfer of risk.

Product Design

Hawa Junior 120 GP Pocket consisting of running track (aluminum wall thickness 3.5 mm (3/4")), running gear with friction bearing rollers, stopper, spring buffer or soft closing mechanism Hawa SoftMove 120, Point fixing of door, bottom guide with zero clearance

Optional:

(...) Set for installable and removable running track

Interfaces

Door leaf- Glass processing for glass holders

– Positive-fit glass fixing with point fixing

Assembly set

– The retainer profile is installed during the creation of the pocket construction

Pocket construction

– Pocket construction must be taken care of by the customer