

Fitting for top-running glass doors up to 160 kg (325 lbs.), with surface mounted running track or running track flush with the ceiling. Ceiling mounting.

Product-Highlights



Aesthetics

Neutral, linear design



Security

Very safe thanks to positive-fit glass fixing

Technical guidelines

Max. Door weight	160 kg (352 lbs.)
Door thickness	8–16 mm (5/16" to 5/8")
Max. Door height	4000 mm (13' 1 15/32")
Max. Door width	3000 mm (9' 10 1/8")
Max. Opening width	2950 mm (9' 8 5/32")
Height adjustable	+/- 3 mm (1/8")
Soft close	No
Door material	Glass

System options

Ceiling mounting	Yes
Ceiling mounting recessed	Yes
Top-running	Yes

Application area

Utilization light / semi-public access	Yes
Utilization medium / semi-public access	Yes
Utilization high / public access	Yes

Tests

Building hardware – Hardware for sliding doors and folding doors according to EN 1527 / 2013
– Duration of functionality: Class 6 (highest class = 100,000 cycles)

Hardware for furniture – Strength and durability of slide fittings for sliding doors and roll fronts according to EN 15706 / 2009

Warranty

With the exception of parts subject to wear and tear, Hawa warrants the flawless functioning of the products delivered by it, as well as the durability of all parts, for a period of 2 years commencing from the transfer of risk.

Product Design

Hawa Junior 160 G consisting of running track (aluminum wall thickness 4.0 mm (5/32")), running gear with friction bearing rollers, stopper, suspension profile with suspension carriage, bottom guide with zero clearance, suspension and glass retaining profiles

Optional:

- (...) Guide track
- (...) Track set for fixed glazing
- (...) Bar bolt lock
- (...) Bottom door stopper, with centering part

Interfaces

Door leaf- Glass processing for glass holders
– Positive-fit glass fixing on suspension and glass retaining profiles