

Fitting for top-running wooden doors up to 250 kg (551 lbs.), with surface mounted running track. Ceiling mounting.

Product-Highlights



Comfort

High quality, long-lasting friction bearing for quiet, smooth running, even with heavier weights



Flexibility

Steel suspension bracket for screw fixing or welding

Technical guidelines

Max. Door weight	250 kg (551 lbs.)
Door thickness	35–80 mm (1 3/8" to 3 5/32")
Max. Door height	4000 mm (13' 1 15/32")
Max. Door width	3000 mm (9' 10 1/8")
Max. Opening width	2950 mm (9' 8 5/32")
Height adjustable	+/- 5 mm (3/16")
Soft close	No
Door material	Wood

System options

Ceiling mounting	Yes
Top-running	Yes

Application area

Utilization light / semi-public access	Yes
Utilization medium / semi-public access	Yes
Utilization high / public access	Yes

Tests
Building hardware – Hardware for sliding doors and folding doors according to EN 1527 / 2013
– Duration of functionality: Class 6 (highest class = 100,000 cycles)

Hardware for furniture – Strength and durability of slide fittings for sliding doors and roll fronts according to EN 15706 / 2009

Warranty
With the exception of parts subject to wear and tear, Hawa warrants the flawless functioning of the products delivered by it, as well as the durability of all parts, for a period of 2 years commencing from the transfer of risk.

Product Design

Hawa Junior 250 A consisting of running track (aluminum wall thickness 4.5 mm (3/16")), running gear with friction bearing rollers, stopper, suspension profile with suspension carriage, bottom guide with zero clearance

Optional:

- (...) Guide track, for groove mounting, plastic
- (...) Bottom door stopper, with centering part
- (...) Wall bottom guide Hawa Confort 160

Interfaces

Door leaf

- Screw fixed or welded attachment of the support flange
- Guide groove (H × B) 25 × 14 mm (31/32" × 9/16") (28 × 17 mm (1 3/32" × 21/32")) with plastic guide track)