

**Fitting for top-running glass doors up to 250 kg (551 lbs.), with surface mounted running track or running track flush with the ceiling. Ceiling mounting.**

**Product-Highlights**



**Comfort**

High quality steel ball bearing rollers for quiet, smooth running, even with heavy weights



**Security**

Very safe thanks to positive-fit glass fixing

**Technical guidelines**

Max. Door weight	250 kg (551 lbs.)
Door thickness	8–16 mm (5/16" to 5/8")
Max. Door height	4000 mm (13' 1 15/32")
Max. Door width	3000 mm (9' 10 1/8")
Max. Opening width	2950 mm (9' 8 5/32")
Height adjustable	+/- 5 mm (3/16")
Soft close	No
Door material	Glass

**System options**

Ceiling mounting	Yes
Ceiling mounting recessed	Yes
Top-running	Yes

**Application area**

Utilization light / semi-public access	Yes
Utilization medium / semi-public access	Yes
Utilization high / public access	Yes

**Tests** Building hardware – Hardware for sliding doors and folding doors according to EN 1527 / 2013  
– Duration of functionality: Class 6 (highest class = 100,000 cycles)

Hardware for furniture – Strength and durability of slide fittings for sliding doors and roll fronts according to EN 15706 / 2009

**Warranty** With the exception of parts subject to wear and tear, Hawa warrants the flawless functioning of the products delivered by it, as well as the durability of all parts, for a period of 2 years commencing from the transfer of risk.

**Product Design**

Hawa Junior 250 G consisting of running track (aluminum wall thickness 4.5 mm (3/16")), running gear with friction bearing rollers, stopper, suspension profile with suspension carriage, bottom guide with zero clearance, suspension and glass retaining profiles

Optional:

- (...) Guide track
- (...) Bar bolt lock
- (...) Bottom door stopper, with centering part
- (...) Connector parts to profiles

**Interfaces**

**Door leaf**

- Glass processing for glass holders
- Positive-fit glass fixing on suspension and glass retaining profiles