

Fitting for top-running wooden doors up to 40 kg (88 lbs.), with surface mounted running track or running track flush with the ceiling. Optionally with soft and self closing mechanism. Ceiling mounting. Minimal installation height. Wall pocket solution.

Product-Highlights



Flexibility

The running track can be installed and removed at any time



Aesthetics

Thanks to integrated spring stop with Push-to-open function, there are no visible hardware components, door milling grooves or spring handles at the edge of the door

Technical guidelines

Max. Door weight	40 kg (88 lbs.)
Door thickness	35–80 mm (1 3/8" to 3 5/32")
Max. Door height	4000 mm (13' 1 15/32")
Max. Door width	1250 mm (4' 1 7/32")
Max. Opening width	1220 mm (4' 1/32")
Height adjustable	+/- 3 mm (1/8")
Soft close	Optional
Door material	Wood

System options

Ceiling mounting	Yes
Ceiling mounting recessed	Yes
Top-running	Yes

Application area

Utilization light / semi-public access	Yes
Utilization medium / semi-public access	Yes
Utilization high / public access	Yes

Tests Building hardware – Hardware for sliding doors and folding doors according to EN 1527 / 2013
– Duration of functionality: Class 6 (highest class = 100,000 cycles)

Hardware for furniture – Strength and durability of slide fittings for sliding doors and roll fronts according to EN 15706 / 2009

Warranty With the exception of parts subject to wear and tear, Hawa warrants the flawless functioning of the products delivered by it, as well as the durability of all parts, for a period of 2 years commencing from the transfer of risk.

Product Design

Hawa Junior 40 B Pocket consisting of running track (aluminum wall thickness 2.0 mm (3/32")), running gear with friction bearing rollers, stopper, spring buffer or soft closing mechanism Hawa SoftMove 40, suspension profile with suspension carriage, bottom guide with zero clearance

Optional:

- (...) Guide track, for groove mounting, plastic
- (...) Set for installable and removable running track

Interfaces

Door leaf

- Recess for suspension profile (H × B) 25 × 20 mm (31/32" × 25/32")
- Screw fixing of the suspension profiles
- Guide groove (H × B) 20 × 10 mm (25/32" × 13/32") (20 × 12 mm (25/32" × 13/32") with plastic guide track)

Pocket construction

- Pocket construction must be taken care of by the customer

Assembly set

- The retainer profile is installed during the creation of the pocket construction