

Fitting for top-running glass doors up to 40 kg (88 lbs.), with surface mounted running track or running track flush with the ceiling. Optionally with soft and self closing mechanism. Wall or ceiling mounting. Minimal installation height.

Product-Highlights



Productivity

Easy height adjustment via both suspensions on completely installed door



Aesthetics

Cover caps in different design versions

Technical guidelines

Max. Door weight	40 kg (88 lbs.)
Door thickness	8–12.7 mm (5/16" to 1/2")
Max. Door height	4000 mm (13' 1 15/32")
Max. Door width	3000 mm (9' 10 1/8")
Max. Opening width	2950 mm (9' 8 5/32")
Height adjustable	+/- 3 mm (1/8")
Soft close	Yes
Door material	Glass

System options

Wall mounting	Yes
Ceiling mounting	Yes
Ceiling mounting recessed	Yes
Top-running	Yes

Application area

Utilization light / semi-public access	Yes
Utilization medium / semi-public access	Yes
Utilization high / public access	Yes

Tests

Building hardware – Hardware for sliding doors and folding doors according to EN 1527 / 2013
– Duration of functionality: Class 6 (highest class = 100,000 cycles)

Hardware for furniture – Strength and durability of slide fittings for sliding doors and roll fronts according to EN 15706 / 2009

Warranty

With the exception of parts subject to wear and tear, Hawa warrants the flawless functioning of the products delivered by it, as well as the durability of all parts, for a period of 2 years commencing from the transfer of risk.

Product Design

Hawa Junior 40 GP consisting of running track (aluminum wall thickness 2.0 mm (3/32")), running gear with friction bearing rollers, stopper or soft closing mechanism Hawa SoftMove 40, Glass suspension with point fixing, bottom guide with zero clearance

Optional:

- (....) Guide tracks
- (....) Track set for fixed glazing
- (....) Bottom door stopper, with centering part

Interfaces

Door leaf

- Glass processing for glass holders
- Positive-fit glass fixing with point fixing