

**Fitting for top-running wooden doors up to 80 kg (176 lbs.), with surface mounted running track or running track flush with the ceiling. Optionally with soft and self closing mechanism. Ceiling mounting. Minimal installation height. Wall pocket solution.**

**Product-Highlights**

**Reliability**

Well-ried product tested for 100,000 cycles, which corresponds to a service life of about 25 years


**Productivity**

Easy height adjustment via both suspensions and convenient depth adjustment of the installed door in the wall pocket

**Technical guidelines**

Max. Door weight	80 kg (176 lbs.)
Door thickness	35–80 mm (1 3/8" to 3 5/32")
Max. Door height	4000 mm (13'1 15/32")
Max. Door width	1500 mm (4'11 1/16")
Max. Opening width	1465 mm (4'9 11/16")
Height adjustable	+/- 3 mm (1/8")
Soft close	Yes
Door material	Wood
Finish color of visible profiles	Aluminum anodized

**System options**

Ceiling mounting	Yes
Ceiling mounting recessed	Yes
Top-running	Yes

**Application area**

Utilization light / semi-public access	Yes
Utilization medium / semi-public access	Yes
Utilization high / public access	Yes

**Tests**

Building hardware – Hardware for sliding doors and folding doors according to EN 1527 / 2013  
 – Duration of functionality: Class 6\* (highest class = 100,000 cycles)  
 \* System without soft closing system has been tested with 200,000 cycles

Hardware for furniture – Strength and durability of slide fittings for sliding doors and roll fronts according EN 15706 / 2009

**Warranty**

With the exception of parts subject to wear and tear, Hawa warrants the flawless functioning of the products delivered by it, as well as the durability of all parts, for a period of 2 years commencing from the transfer of risk.

**Product Design**

Hawa Junior 80 B Pocket consisting of running track (aluminum wall thickness 2.9 mm (1/8")), running gear with friction bearing rollers, stopper, spring buffer or soft closing mechanism Hawa SoftMove 80, suspension profile with suspension carriage, bottom guide with zero clearance

Optional:

- (...) Guide track, for groove mounting, plastic
- (...) Set for installable and removable running track
- (...) Clip-on panel for retainer profile, for lintel panelling, aluminum

**Interfaces**

**Door leaf**

- Recess for suspension profile (H × W) 25 × 22 mm (31/32" × 7/8")
- Screw fixing of the suspension profiles
- Guide groove (H × B) 20 × 10 mm (25/32" × 13/32") (20 × 12 mm (25/32" × 15/32") with plastic guide track)

**Pocket construction**

- Pocket construction must be taken care of by the customer

**Assembly set**

- The retainer profile is installed during the creation of the pocket construction