

Fitting for top-running glass doors up to 80 kg (176 lbs.), with surface mounted running track. Optionally with soft and self closing mechanism. Wall or ceiling mounting.

Product-Highlights



Productivity

Easy clamping mounting of the glass door to the suspension without a glass cut-out



Comfort

Very quiet running and smooth sliding with high quality soft and self closing system

Technical guidelines

| | |
|--------------------|---------------------------|
| Max. Door weight | 80 kg (176 lbs.) |
| Door thickness | 8–12.7 mm (5/16" to 1/2") |
| Max. Door height | 4000 mm (13' 1 15/32") |
| Max. Door width | 3000 mm (9' 10 1/8") |
| Max. Opening width | 2950 mm (9' 8 5/32") |
| Height adjustable | +/- 3 mm (1/8") |
| Soft close | Yes |
| Door material | Glass |

System options

| | |
|------------------|-----|
| Wall mounting | Yes |
| Ceiling mounting | Yes |
| Top-running | Yes |

Application area

| | |
|---|-----|
| Utilization light / semi-public access | Yes |
| Utilization medium / semi-public access | Yes |
| Utilization high / public access | Yes |

Tests

Building hardware – Hardware for sliding doors and folding doors according to EN 1527 / 2013
– Duration of functionality: Class 6 (highest class = 100,000 cycles)

Hardware for furniture – Strength and durability of slide fittings for sliding doors and roll fronts according to EN 15706 / 2009

Warranty

With the exception of parts subject to wear and tear, Hawa warrants the flawless functioning of the products delivered by it, as well as the durability of all parts, for a period of 2 years commencing from the transfer of risk.

Product Design

Hawa Junior 80 GS consisting of running track (aluminum wall thickness 2.9 mm (1/8")), running gear with friction bearing rollers, stopper or soft closing mechanism Hawa SoftMove 80, Clamping shoe with hanger bolt, bottom guide with zero clearance

Optional:

(...) Guide tracks

(...) Bottom door stopper, with centering part

Interfaces

Door leaf

- No recess

- Clamped glass fixing