

**Fitting for top-running glass doors up to 80 kg (176 lbs.), with surface mounted running track. Optionally with soft and self closing mechanism. Ceiling mounting. Wall pocket solution.**

**Product-Highlights**



**Productivity**

Easy clamping mounting of the glass door to the suspension without a glass cut-out



**Aesthetics**

The integrated spring stop gently pushes open sliding doors that are completely recessed in the wall pocket

**Technical guidelines**

Max. Door weight	80 kg (176 lbs.)
Door thickness	8–12.7 mm (5/16" to 1/2")
Max. Door height	4000 mm (13' 1 15/32")
Max. Door width	1200 mm (3' 11 1/4")
Max. Opening width	1470 mm (4' 9 7/8")
Height adjustable	+/- 3 mm (1/8")
Soft close	Yes
Door material	Glass

**System options**

Ceiling mounting	Yes
Top-running	Yes

**Application area**

Utilization light / semi-public access	Yes
Utilization medium / semi-public access	Yes
Utilization high / public access	Yes

**Tests** Building hardware – Hardware for sliding doors and folding doors according to EN 1527 / 2013 – Duration of functionality: Class 6 (highest class = 100,000 cycles)

Hardware for furniture – Strength and durability of slide fittings for sliding doors and roll fronts according to EN 15706 / 2009

**Warranty** With the exception of parts subject to wear and tear, Hawa warrants the flawless functioning of the products delivered by it, as well as the durability of all parts, for a period of 2 years commencing from the transfer of risk.

**Product Design**

Hawa Junior 80 GS Pocket consisting of running track (aluminum wall thickness 2.9 mm (1/8")), running gear with friction bearing rollers, stopper, spring buffer or soft closing mechanism Hawa SoftMove 80, Clamping shoe with hanger bolt, bottom guide with zero clearance

Optional:

(...) Set for installable and removable running track

**Interfaces**

**Door leaf**

- No recess
- Clamped glass fixing

**Pocket construction**

- Pocket construction must be taken care of by the customer

**Assembly set**

- The retainer profile is installed during the creation of the pocket construction