

Fitting for 2 telescopic opening glass doors up to 80 kg (176 lbs.), with surface mounted running track. Ceiling mounting.

Product-Highlights



Flexibility

Door openings up to 3000 mm (9'10 1/8'') wide



Flexibility

Telescopic opening without guide track

Technical guidelines

Max. Door weight	80 kg (176 lbs.)
Door thickness	8–16 mm (5/16" to 5/8") (Fully tempered monolithic glass (ESG))
Max. Door height	2600 mm (8' 6 3/8'')
Door width	500–1000 mm (1' 7 11/16" to 3' 3 3/8'')
Max. Opening width	3700 mm (12' 1 21/32'')
Height adjustable	+/- 2 mm (3/32'')
Soft close	No
Door material	Glass

System options

Ceiling mounting	Yes
Top-running	Yes

Application area

Utilization light / semi-public access	Yes
Utilization medium / semi-public access	Yes
Utilization high / public access	Yes

Tests

Building hardware – Hardware for sliding doors and folding doors according to EN 1527 / 2013
– Duration of functionality: Class 6 (highest class = 100,000 cycles)

Hardware for furniture – Strength and durability of slide fittings for sliding doors and roll fronts according to EN 15706 / 2009

Warranty

With the exception of parts subject to wear and tear, Hawa warrants the flawless functioning of the products delivered by it, as well as the durability of all parts, for a period of 2 years commencing from the transfer of risk.

Product Design

Hawa Junior 80 G Telescopic consisting of running track (aluminum wall thickness 2.9 mm (1/8")), running gear with friction bearing rollers, stopper, toothed belt with deflection rollers, suspension profile with suspension carriage, bottom guide with zero clearance, suspension and glass retaining profiles

Optional:

- (....) Guide track
- (....) Running track set with fixed glazing
- (....) Bottom door stopper, with centering part

Interfaces

Door leaf

- Glass processing for glass holders
- Positive-fit glass fixing on suspension and glass retaining profiles