

**Fitting for top-running metal doors up to 80 kg (176 lbs.), with surface mounted running track or running track flush with the ceiling. Optionally with soft closing mechanism. Wall or ceiling mounting.**

**Product-Highlights**



**Aesthetics**

Neutral, linear design



**Security**

Very safe thanks to positive-fit glass fixing in metal door frame

**Technical guidelines**

Max. Door weight	80 kg (176 lbs.)
Door thickness	35–80 mm (1 3/8" to 3 5/32")
Max. Door height	4000 mm (13' 1 15/32")
Max. Door width	3000 mm (9' 10 1/8")
Max. Opening width	2950 mm (9' 8 5/32")
Height adjustable	+/- 4 mm (5/32")
Soft close	Yes
Door material	Metal

**System options**

Wall mounting	Yes
Ceiling mounting	Yes
Top-running	Yes

**Application area**

Utilization medium / semi-public access	Yes
Utilization high / public access	Yes

**Tests**

Building hardware – Hardware for sliding doors and folding doors according to EN 1527 / 2013  
– Duration of functionality: Class 6 (highest class = 100,000 cycles)

Hardware for furniture – Strength and durability of slide fittings for sliding doors and roll fronts according to EN 15706 / 2009

**Warranty**

With the exception of parts subject to wear and tear, Hawa warrants the flawless functioning of the products delivered by it, as well as the durability of all parts, for a period of 2 years commencing from the transfer of risk.

**Product Design**

Hawa Junior 80 M consisting of running track (aluminum wall thickness 2.9 mm (1/8")), running gear with friction bearing rollers, stopper or soft closing mechanism Hawa SoftMove 80, hanger bracket, bottom guide

Optional:

(...) Guide track

(...) Bottom door stopper, with centering part

**Interfaces**

**Door leaf**

– Screw fixing of the hanger bracket