

# Fitting for 2 telescopic opening wooden doors up to 80 kg (176 lbs.), with surface mounted running track. Ceiling mounting.

Product-Highlights	Flexibility Door openings	up to 3200 mm (10' 5 31/32'') possible
	Flexibility Combination of	telescopic and symmetrical opening possible
Technical guidelines	Max. Door weight	80 kg (176 lbs.)
	Door thickness	32-47 mm (1 1/4" to 1 27/32")
	Max. Door height	4000 mm (13' 1 15/32'')
	Door width	500–1200 mm (1' 7 11/16'' to 3' 11 1/4'')
	Max. Opening width	4500 mm (14' 9 5/32'')
	Height adjustable	+/- 2 mm (3/32'')
	Soft close	No
	Door material	Wood
System options	Ceiling mounting	Yes
	Top-running	Yes
Application area	Utilization light / semi-public access	Yes
	Utilization medium / semi-public acces	ss Yes
	Utilization high / public access	Yes

**Tests** Building hardware – Hardware for sliding doors and folding doors according to EN 1527 / 2013

- Duration of functionality: Class 6\* (highest class = 100,000 cycles)

Hardware for furniture – Strength and durability of slide fittings for sliding doors and roll fronts

according to EN 15706 / 2009

Warranty With the exception of parts subject to wear and tear, Hawa warrants the flawless

functioning of the products delivered by it, as well as the durability of all parts, for a period

of 2 years commencing from the transfer of risk.



Hawa Junior 80 Z Telescopic 2

## **Product Design**

Hawa Junior 80 Z Telescopic 2 consisting of running track (aluminum wall thickness 2.9 mm (1/8'')), running gear with friction bearing rollers, stopper, toothed belt with deflection rollers, bottom guide with zero clearance

### Optional:

(....) Guide track, for groove mounting, plastic (....) Bottom door stopper, with centering part

#### Interfaces

#### **Door leaf**

- Screw fixing of the two-way suspension
- Guide groove (H  $\times$  B) 25  $\times$  10 mm (31/32''  $\times$  13/32'') (20  $\times$  12 mm (25/32''  $\times$  15/32'') with plastic guide track)