

Fitting for 4 telescopic opening wooden doors up to 40 kg (88 lbs.), with surface mounted running track. Ceiling mounting.

Product-Highlights



Flexibility

Door openings up to 3200 mm (10' 5 31/32") possible



Flexibility

Combination of telescopic and symmetrical opening possible

Technical guidelines

Max. Door weight	40 kg (88 lbs.)
Door thickness	40–47 mm (1 9/16" to 1 27/32")
Max. Door height	4000 mm (13' 1 15/32")
Door width	500–800 mm (1' 7 11/16" to 2' 7 1/2")
Max. Opening width	2900 mm (9' 6 3/16")
Height adjustable	+/- 2 mm (3/32")
Door material	Wood

Application area

Utilization light / semi-public access	Yes
Utilization medium / semi-public access	Yes
Utilization high / public access	Yes

Tests Building hardware – Hardware for sliding doors and folding doors according to EN 1527 / 2013
– Duration of functionality: Class 6 (highest class = 100,000 cycles)

Hardware for furniture – Strength and durability of slide fittings for sliding doors and roll fronts according to EN 15706 / 2009

Warranty With the exception of parts subject to wear and tear, Hawa warrants the flawless functioning of the products delivered by it, as well as the durability of all parts, for a period of 2 years commencing from the transfer of risk.

Product Design

Hawa Junior 80 Z Telescopic 4 consisting of running track (aluminum wall thickness 2.9 mm (1/8")), running gear with friction bearing rollers, stopper, toothed belt with deflection rollers, two-way suspension, bottom guide with zero clearance

Optional:

(...) Guide track, for groove mounting, plastic

(...) Bottom door stopper, with centering part

Interfaces

Door leaf

– Screw fixing of the two-way suspension

– Guide groove (H × B) 25 × 10 mm (31/32" × 13/32") (20 × 12 mm (25/32" × 15/32") with plastic guide track)