

Fitting for top-running wooden or glass doors up to 70 kg (154 lbs.), with surface mounted running track or guide track flush with the ceiling. Ceiling mounting.

Product-Highlights



Comfort

Sprung bottom guide on continuous guide track for stable and quiet sliding characteristics



Aesthetics

Filigree running track and minimal installation height for sophisticated design requirements

Technical guidelines

Max. Door weight	70 kg (154 lbs.)
Door thickness	30–40 mm (1 3/16" to 1 9/16")
Max. Door height	2600 mm (8' 6 3/8")
Max. Door width	3000 mm (9' 10 1/8")
Max. Opening width	2950 mm (9' 8 5/32")
Height adjustable	+/- 3 mm (1/8")
Soft close	No
Door material	Wood;Glass;Wood Glass Mix
Finish color of visible profiles	Aluminum raw;Aluminum anodized / aluminum stainless steel effect

System options

Ceiling mounting	Yes
Ceiling mounting recessed	Yes
Top-running	Yes

Application area

Utilization light / semi-public access	Yes
Utilization medium / semi-public access	Yes

Warranty

With the exception of parts subject to wear and tear, Hawa warrants the flawless functioning of the products delivered by it, as well as the durability of all parts, for a period of 2 years commencing from the transfer of risk.

Product Design

Hawa Ordena 70 F consisting of running track, running gear with ball bearing rollers, suspension profile for wood or point fixing for glass, track buffer with retention spring, spring-loaded bottom guide, guide track

Optional:

- (...) Double running track
- (...) Double guide track
- (...) Cover caps
- (...) Wall connection profile
- (...) Edge protection

Interfaces

Wooden door leaf

- Recess for housing (H × W) 25 × 20 mm (31/32" x 25/32")
- Screwed-on housing
- Drilled-in bottom guide Ø 12 mm (15/32")

Glass door leaf

- Glass processing for glass holder at top and bottom