

Fitting for top-running glass doors up to 100 kg (220 lbs.), with surface mounted running track. Optionally with soft and self closing mechanism. Wall or ceiling mounting. With fixed glass support profile.

Product-Highlights



Comfort

Smooth, quiet sliding and gentle stopping of the door with integrated soft and self closing system



Aesthetics

Large glass systems can be implemented as passage or room doors

Technical guidelines

| | |
|--------------------|---------------------------|
| Max. Door weight | 100 kg (220 lbs.) |
| Door thickness | 8–12.7 mm (5/16" to 1/2") |
| Max. Door height | 2700 mm (8' 10 5/16") |
| Max. Door width | 1600 mm (5' 3") |
| Max. Opening width | 1550 mm (5' 1 1/32") |
| Height adjustable | +/- 4 (5/32") |
| Soft close | Yes |
| Door material | Glass |

System options

| | |
|------------------|-----|
| Wall mounting | Yes |
| Ceiling mounting | Yes |
| Top-running | Yes |

Application area

| | |
|---|-----|
| Utilization light / semi-public access | Yes |
| Utilization medium / semi-public access | Yes |
| Utilization high / public access | Yes |

Tests Building hardware – Hardware for sliding doors and folding doors according to DIN EN 1527
– Duration of functionality: Class 6 (highest class = 100,000 cycles)

Hardware for furniture – Roller fittings for sliding doors according to DIN 68859
– Stop reliability
– Retention reliability

Warranty With the exception of parts subject to wear and tear, Hawa warrants the flawless functioning of the products delivered by it, as well as the durability of all parts, for a period of 2 years commencing from the transfer of risk.

Product Design

Hawa Porta 100 GF consisting of running track with fixed glass profile, clip-on, running gear with ball bearing rollers, stopper with retention spring, clamping shoe with hanger bolt, bottom guide with zero clearance

Optional:

(...) Hawa Porta 100 soft and self closing mechanism

(...) Wall compensation profile

(...) Bottom door stopper, with centering part

Interfaces

Door leaf

- No recess

- Clamped glass fixing