

**Fitting for 2 synchronously opening glass doors up to 100 kg (220 lbs.), with surface mounted running track or running track flush with the ceiling. Wall or ceiling mounting.**

### Product-Highlights



#### Flexibility

Standard applications can be extended with the Synchro option



#### Comfort

Two simultaneously sliding doors make large, fully accessible openings possible

### Technical guidelines

Max. Door weight	100 kg (220 lbs.)
Door thickness	8–12.7 mm (5/16" to 1/2")
Max. Door height	2700 mm (8' 10 5/16")
Max. Door width	1200 mm (3' 11 1/4")
Max. Opening width	2300 mm (7' 6 9/16")
Height adjustable	+/- 3 mm (1/8")
Soft close	No
Door material	Glass

### System options

Wall mounting	Yes
Ceiling mounting	Yes
Ceiling mounting recessed	Yes
Top-running	Yes

### Application area

Utilization light / semi-public access	Yes
Utilization medium / semi-public access	Yes
Utilization high / public access	Yes

### Tests

Building hardware – Hardware for sliding doors and folding doors according to DIN EN 1527  
– Duration of functionality: Class 6 (highest class = 100,000 cycles)

Hardware for furniture – Roller fittings for sliding doors according to DIN 68859  
– Stop reliability  
– Retention reliability

### Warranty

With the exception of parts subject to wear and tear, Hawa warrants the flawless functioning of the products delivered by it, as well as the durability of all parts, for a period of 2 years commencing from the transfer of risk.

**Product Design**

Hawa Porta 100 GW Synchro consisting of running track (aluminum), clip-on, running gear with ball bearing rollers, stopper with retention spring, kevlar rope with deflection rollers, clamping shoe with hanger bolt, bottom guide with zero clearance

Optional:

- (....) Wall mounted angled profile with screw set
- (....) Bottom guide set for wall mounting, with roller
- (....) Bottom door stopper, with centering part

**Interfaces**

**Door leaf**

- No recess
- Clamped glass fixing