

**Fitting for 2 synchronously opening glass doors up to 100 kg (220 lbs.), with surface mounted running track. Wall or ceiling mounting.**

**Product-Highlights**



**Flexibility**

Standard applications can be extended with the Synchro option



**Comfort**

Two simultaneously sliding doors make large, fully accessible openings possible

**Technical guidelines**

Max. Door weight	100 kg (220 lbs.)
Door thickness	8–12.7 mm (5/16" to 1/2")
Max. Door height	2700 mm (8' 10 5/16")
Max. Door width	1200 mm (3' 11 1/4")
Max. Opening width	1150 mm (3' 9 9/32")
Height adjustable	+/- 4 mm (5/32")
Soft close	No
Door material	Glass

**System options**

Wall mounting	Yes
Ceiling mounting	Yes
Top-running	Yes

**Application area**

Utilization light / semi-public access	Yes
Utilization medium / semi-public access	Yes
Utilization high / public access	Yes

- Tests**
- Building hardware – Hardware for sliding doors and folding doors according to DIN EN 1527
  - Duration of functionality: Class 6 (highest class = 100,000 cycles)
  - Hardware for furniture – Roller fittings for sliding doors according to DIN 68859
  - Stop reliability
  - Retention reliability

**Warranty** With the exception of parts subject to wear and tear, Hawa warrants the flawless functioning of the products delivered by it, as well as the durability of all parts, for a period of 2 years commencing from the transfer of risk.

**Product Design**

Hawa Porta 100 G Synchro consisting of running track (aluminum), clip-on panel, running gear with ball bearing rollers, stopper with retention spring, kevlar rope with deflection rollers, clamping shoe with hanger bolt, bottom guide with roller

Optional:

(...) Bottom guide set for wall mounting, with roller

(...) Bottom door stopper, with centering part

**Interfaces**

**Door leaf**

- No recess
- Clamped glass fixing