




**Fitting for top-running wooden doors up to 100 kg (220 lbs.), with surface mounted running track. Optionally with soft and self closing mechanism. Wall mounting. Minimal installation height.**

<b>Product-Highlights</b>	 <b>Flexibility</b>	Aluminium panel or customer-provided wooden panelling integrated in the system
	 <b>Productivity</b>	Tool-less door mounting
	 <b>Aesthetics</b>	Also available in black as a “Black Edition” design option for a particularly attractive appearance

<b>Technical guidelines</b>	Max. Door weight	100 kg (220 lbs.)
	Door thickness	30–45 mm (1 3/16" to 1 25/32")
	Max. Door height	2700 mm (8' 10 5/16")
	Max. Door width	1600 mm (5' 3")
	Max. Opening width	1535 mm (5' 7/16")
	Height adjustable	+/- 3 mm (1/8")
	Soft close	Yes
	Door material	Wood
	Finish color of visible profiles	Aluminum / aluminum anodized / aluminum black anodized
<b>System options</b>	Wall mounting	Yes
	Top-running	Yes
<b>Application area</b>	Utilization light / semi-public access	Yes
	Utilization medium / semi-public access	Yes
	Utilization high / public access	Yes

<b>Tests</b>	Building hardware – Hardware for sliding doors and folding doors according to EN 1527 – Duration of functionality: Class 6 (highest class = 100,000 cycles)
	Hardware for furniture – Roller fittings for sliding doors according to DIN 68859 – Stop reliability – Retention reliability

<b>Warranty</b>	With the exception of parts subject to wear and tear, Hawa warrants the flawless functioning of the products delivered by it, as well as the durability of all parts, for a period of 2 years commencing from the transfer of risk.
-----------------	---

**Product Design**

Hawa Porta 100 HMD consisting of running track, running gear with ball bearing rollers, stopper with retention spring, running gear support, bottom guide with roller

Optional:

- (...) Running track with extended spacing of +9 mm/+20 mm (+11/32"/+25/32")
- (...) Clip-on panel, wall mounting, aluminum
- (...) Hawa Porta 100 soft and self closing mechanism
- (...) Cover cap for assembly opening
- (...) Bottom guide set for wall mounting, with roller

**Interfaces**

**Door leaf**

- Recess for housing (H × W) 23 × 18 mm (29/32" × 23/32")
- Screw fixing of the housing
- Guide groove (H × W) 16 × 12 mm (5/8" × 15/32")