

Fitting for 2 synchronously opening wooden doors up to 100 kg (220 lbs.), with surface mounted running track. Wall or ceiling mounting.

Product-Highlights



Flexibility

Standard applications can be extended with the Synchro option



Comfort

Two doors open simultaneously and make large openings possible



Aesthetics

Also available in black as a "Black Edition" design option for a particularly attractive appearance

Technical guidelines

Max. Door weight	100 kg (220 lbs.)
Door thickness	30–80 mm (1 3/16" to 3 5/32")
Max. Door height	2700 mm (8' 10 5/16")
Max. Door width	1200 mm (3' 11 1/4")
Max. Opening width	2300 mm (7' 6 9/16")
Height adjustable	+/- 3 mm (1/8")
Soft close	No
Door material	Wood

System options

Ceiling mounting	Yes
Top-running	Yes

Application area

Utilization light / semi-public access	Yes
Utilization medium / semi-public access	Yes
Utilization high / public access	Yes

Tests

Building hardware – Hardware for sliding doors and folding doors according to DIN EN 1527
– Duration of functionality: Class 6 (highest class = 100,000 cycles)

Hardware for furniture – Roller fittings for sliding doors according to DIN 68859
– Stop reliability
– Retention reliability

Warranty

With the exception of parts subject to wear and tear, Hawa warrants the flawless functioning of the products delivered by it, as well as the durability of all parts, for a period of 2 years commencing from the transfer of risk.

Product Design

Hawa Porta 100 H Synchro consisting of running track (aluminum), clip-on panel, running gear with ball bearing rollers, stopper with retention spring, kevlar rope with deflection rollers, support flange, bottom guide with roller

Optional:

(...) Hawa Porta 60/100 assembly set

(...) Clip-on component, for wooden and aluminum panel

Interfaces

Door leaf

- Screw fixing of the support flange
- Guide groove (H × W) 16 × 12 mm (5/8" × 15/32")