

**Fitting for top-running wooden doors up to 300 kg (660 lbs.), with surface mounted running track. Wall or ceiling mounting.**

**Product-Highlights**



**Flexibility**

Three or four point guidance for maximum stability



**Comfort**

Even heavy doors close smoothly and quietly thanks to the ball bearing rollers

**Technical guidelines**

Max. Door weight	300 kg (660 lbs.)
Door thickness	40-80 mm (1 9/16" to 3 5/32")
Max. Door height	4000 mm (13' 1 15/32")
Max. Door width	4000 mm (13' 1 15/32")
Max. Opening width	3950 mm (12' 11 1/2")
Height adjustable	+10 / -5 mm (+13/32" / -3/16")
Soft close	No
Door material	Wood

**System options**

Wall mounting	Yes
Ceiling mounting	Yes
Top-running	Yes

**Application area**

Utilization light / semi-public access	Yes
Utilization medium / semi-public access	Yes
Utilization high / public access	Yes

- Tests**
- Building hardware – Hardware for sliding doors and folding doors according to DIN EN 1527
  - Duration of functionality: Class 6 (highest class = 100,000 cycles)
  - Hardware for furniture – Roller fittings for sliding doors according to DIN 68859
  - Stop reliability
  - Retention reliability

**Warranty** With the exception of parts subject to wear and tear, Hawa warrants the flawless functioning of the products delivered by it, as well as the durability of all parts, for a period of 2 years commencing from the transfer of risk.

**Product Design**

Hawa Porta 300 H consisting of running track (steel or aluminum), running gear with ball bearing rollers, stopper with rubber buffer, support flange, bottom door stopper

Optional:

- (...) Guide track steel
- (...) Bracket set for wall mounting
- (...) Support bracket for bottom guide
- (...) Track connection

**Interfaces**

**Door leaf**

- Screw fixed or welded attachment of the support flange
- Guide groove (H × W) 25 × 7 mm (31/32" × 9/32") (25 × 25 mm (31/32" × 31/32") with steel guide track)