



Fitting for top-running glass doors up to 40 kg (88 lbs.), with surface mounted running track. Glass panel installation.

Product-Highlights  **Flexibility** Mounting on solid walls or glass walls with optional glass wall adapters

 **Productivity** No glass processing thanks to clamping shoe connection

Technical guidelines	Max. Door weight	40 kg (88 lbs.)
	Door thickness	8 mm (5/16")
	Max. Door height	2200 mm (7' 2 5/8")
	Max. Door width	1000 mm (3' 3 3/8")
	Max. Opening width	950 mm (3' 1 13/32")
	Height adjustable	+4/-1 (+5/32"/-1/32")
	Soft close	Yes
	Door material	Glass
	Finish color of visible profiles	Aluminum anodized / aluminum stainless steel effect
System options	Wall mounting	Yes
	Top-running	Yes
Application area	Utilization light / semi-public access	Yes
	Utilization medium / semi-public access	Yes

Tests

Building hardware – Hardware for sliding doors and folding doors according to EN 1527
 – Duration of functionality: Class 6 (highest class = 100,000 cycles)

Hardware for furniture – Roller fittings for sliding doors according to DIN 68859
 – Stop reliability
 – Retention reliability

Warranty

With the exception of parts subject to wear and tear, Hawa warrants the flawless functioning of the products delivered by it, as well as the durability of all parts, for a period of 2 years commencing from the transfer of risk.

Product Design

Hawa Porta 40 GE Glass panel installation consisting of running track with glass wall mounting set (aluminum), clip-on panel, running gear with ball bearing rollers, stopper, clamping shoe with hanger bolt, bottom guide

Optional:

(...) Hawa Porta 40 soft and self closing mechanism

Interfaces

Door leaf

- Recess for support holder
- Clamped glass fixing