

**Fitting for top-running wooden doors up to 40 kg (88 lbs.), with surface mounted running track. Optionally with soft and self closing mechanism. Wall mounting.**

**Product-Highlights**

**Flexibility**

Multi-faceted product range, same parts for wooden and glass solutions


**Productivity**

No door processing, continuous adjustment for minimal production times

**Technical guidelines**

Max. Door weight	40 kg (88 lbs.)
Door thickness	18–30 mm (23/32" to 1 3/16")
Max. Door height	2200 mm (7' 2 5/8")
Max. Door width	1000 mm (3' 3 3/8")
Max. Opening width	950 mm (3' 1 13/32")
Height adjustable	+2/-1 mm (+3/32"/-1/32")
Soft close	Yes
Door material	Wood
Finish color of visible profiles	Aluminum anodized / aluminum stainless steel effect

**System options**

Wall mounting	Yes
Top-running	Yes

**Application area**

Utilization light / semi-public access	Yes
Utilization medium / semi-public access	Yes

**Tests**

Building hardware – Hardware for sliding doors and folding doors according to EN 1527  
– Duration of functionality: Class 6 (highest class = 100,000 cycles)

Hardware for furniture – Roller fittings for sliding doors according to DIN 68859  
– Stop reliability  
– Retention reliability

**Warranty**

With the exception of parts subject to wear and tear, Hawa warrants the flawless functioning of the products delivered by it, as well as the durability of all parts, for a period of 2 years commencing from the transfer of risk.

**Product Design**

Hawa Porta 40 H consisting of running track (aluminum), clip-on panel, running gear with friction bearing rollers, stopper, support flange, bottom guide

Optional:

(...) Spacer track

Hawa Porta 40 soft and self closing mechanism

**Interfaces**

**Door leaf**

– Screw fixing of the support flange