



Fitting for top-running wooden doors up to 45 kg (99 lbs.), with surface mounted running track. Wall or ceiling mounting.

Product-Highlights	Flexibility Wall and ceiling mounting	Wall and ceiling mounting to the same system with accessories	
	Productivity Easy processing for minim	al production and installation times	
Technical guidelines	Max. Door weight Door thickness Max. Door height Max. Door width Max. Opening width Height adjustable Soft close Door material Finish color of visible profiles	45 kg (99 lbs.) 30–45 mm (1 3/16'' to 1 25/32'') 2200 mm (7' 2 5/8'') 1000 mm (3' 3 3/8'') 950 mm (3' 1 13/32'') +/- 3 mm (1/8'') No Wood Aluminum anodized	
System options Application area	Wall mounting Ceiling mounting Top-running Utilization light / semi-public access Utilization medium / semi-public access	Yes Yes Yes Yes Yes	
Tests	Building hardware – Hardware for sliding doors and folding doors according to EN 1527 – Duration of functionality: Class 6 (highest class = 100,000 cycles) Hardware for furniture – Roller fittings for sliding doors according to DIN 68859 – Stop reliability – Retention reliability		
Warranty	With the exception of parts subject to wear and tear, Hawa warrants the flawless functioning of the products delivered by it, as well as the durability of all parts, for a period of 2 years commencing from the transfer of risk.		





Product Design	Hawa Porta 45 H consisting of running track (aluminum), running gear with friction bearing rollers, stopper with retention spring, support flange, bottom guide
	Optional: () Bracket set for wall mounting

(....) Bottom guide set for wall mounting, with roller

Interfaces

Door leaf

- Screw fixing of the support flange