

**Fitting for top-running wooden doors up to 60 kg (132 lbs.), with surface mounted running track. Sound attenuation. Wall mounting. Minimal installation height.**

**Product-Highlights**



**Comfort**

Outstanding living comfort thanks to effective exclusion of sound, drafts, odors and unwanted light incidence



**Flexibility**

Aluminium panel or customer-provided wooden panelling integrated in the system



**Productivity**

Tool-less door mounting

**Technical guidelines**

Max. Door weight	60 kg (132 lbs.)
Door thickness	39–45 mm (1 17/32" to 1 25/32")
Max. Door height	2500 mm (8' 2 7/16")
Door width	750–1250 mm (2' 5 17/32" to 4' 1 7/32")
	Inside clearance (LMB)
Max. Opening width	1250 mm (4' 1 7/32")
Height adjustable	+/- 2 mm
Soft close	No
Door material	Wood
Finish color of visible profiles	Aluminum anodized

**System options**

Wall mounting	Yes
Top-running	Yes

**Application area**

Utilization light / semi-public access	Yes
Utilization medium / semi-public access	Yes
Utilization high / public access	Yes

**Tests** Building hardware – Hardware for sliding doors and folding doors according to EN 1527 / 2020  
– Duration of functionality: Class 6 (highest class = 100,000 cycles)

**Warranty** With the exception of parts subject to wear and tear, Hawa warrants the flawless functioning of the products delivered by it, as well as the durability of all parts, for a period of 2 years commencing from the transfer of risk.

### Product Design

Hawa Porta 60 HMD Acoustics consisting of running track, running gear with friction bearing rollers, SoftStop, stopper with retention spring, running gear support, horizontal seal set, vertical seal.

Optional:

(...) Running track with extended spacing of +9 mm/+20 mm (+11/32"/+25/32")

(...) Clip-on panel, wall mounting, aluminum

(...) Cover cap, plastic

### Interfaces

#### Door leaf

- Suspension profile and sealing groove, top (H × W) 30 × 27 mm (1 3/16" × 1 1/16")
- Guide and sealing groove, bottom (H × W) 30 × 23 mm (1 3/16" × 29/32")
- Screw fixing of the suspension profiles and horizontal seals
- Groove for seal, vertical 4 × 4 mm (5/32" × 5/32")

#### Vertical seal level

- Leading surface for vertical seal must be provided by the customer (min. 6 mm (1/4") distance from wall structure)

#### Gap size to floor

- Air gaps of 8–12 mm (5/16" to 15/32") can be taken up by the seal