

Fitting for 1 top-running glass door up to 150 kg (330 lbs.), with concealed suspension. Ceiling mounting.

Product-Highlights	K Flexibility	Only system available on the market for room dividers with single-sided fixed glass components or door pockets in wood and glass	
	Productivity		ng system and special profiles for easy cks in concreted and suspended ceilings
Technical guidelines	Max. Door weight		150 kg (330 lbs.)
, and the second s	Door thickness		8–12.7 mm (5/16'' to 1/2'')
	Max. Door height		3000 mm (9' 10 1/8'')
	Max. Door width		3000 mm (9' 10 1/8'')
	Max. Opening width		2950 mm (9' 8 5/32'')
	Height adjustable		+/- 2.5 mm (3/32'')
	Soft close		No
	Door material		Glass
	Finish color of visible profiles		Aluminum anodized;Aluminum anodized
			/ aluminum stainless steel effect
System options	Ceiling mounting		Yes
	Ceiling mounting recessed		Yes
	Top-running		Yes
Application area	Utilization light / semi-public access		Yes
	Utilization medium / semi-public access		Yes
	Utilization high / public access		Yes
Tests	Building hardware – Hardware for sliding doors and folding doors according to EN 1527 / 1998 – Duration of functionality: Class 3 = 100,000 cycles DIN 68859		
	Hardware for furniture – Roller fittings for sliding doors according to DIN 68859		
Warranty	With the exception of parts subject to wear and tear, Hawa warrants the flawless functioning of the products delivered by it, as well as the durability of all parts, for a period of 2 years commencing from the transfer of risk.		





Product DesignHawa Puro 150 consisting of running track (aluminum), running gear with ball bearing rollers,
suspension wedge, track buffer, floor guide with zero clearance

Optional:

- (....) Guide profile
- (....) Bottom guide for guide profile
- (....) Hawa Toplock lock
- (....) Ceiling connection profile
- (....) Hawa Adapto 100 concrete casting profile
- (....) Wall connection profile
- (....) Vertical sealing profiles
- (....) Bottom door stopper
- (....) Fixing set for fixed woodenelement

Interfaces

Door leaf

- Glass processing for suspension

Fixed element

- Fixed element available in wood or glass

Hawa Adapto concrete casting system

 The Hawa Adapto 120 concrete casting system is already integrated in the concrete ceiling of the building shell