

Fitting for 1 top-running glass door up to 80 kg (176 lbs.), with surface mounted running track or running track flush with the ceiling. With soft and self closing mechanism. Wall or ceiling mounting.

Product-Highlights



Productivity

Suspension wedges accessible from below at any time for extremely quick and easy door mounting and height adjustment



Aesthetics

Technology integrated in the running track makes all-glass solutions possible without visible fitting parts.

Technical guidelines

Max. Door weight	80 kg (176 lbs.)
Door thickness	8–12.7 mm (5/16" to 1/2")
Max. Door height	3000 mm (9' 10 1/8")
Max. Door width	3000 mm (9' 10 1/8")
Max. opening width	2900 mm (9' 6 3/16")
Height adjustable	+/- 3 mm (1/8")
Soft close	Yes
Door material	Glass
Finish color of visible profiles	Aluminum anodized; Aluminum anodized / aluminum stainless steel effect

System options

Wall mounting	Yes
Ceiling mounting	Yes
Ceiling mounting recessed	Yes
Top-running	Yes

Application area

Utilization light / semi-public access	Yes
Utilization medium / semi-public access	Yes
Utilization high / public access	Yes

Tests

Building hardware - Hardware for sliding doors and folding doors according to EN 1527/ 2013
– Duration of functionality and overloading class 3 = 100,000 cycles EN 15706: 2008

Hardware for furniture – Roller fittings for sliding doors according to DIN 68859

Warranty

With the exception of parts subject to wear and tear, Hawa warrants the flawless functioning of the products delivered by it, as well as the durability of all parts, for a period of 2 years commencing from the transfer of risk.

Hawa Sliding Solutions AG

Untere Fischbachstrasse 4, 8932 Mettmenstetten, Switzerland
Phone +41 44 787 17 17, info@hawa.com, www.hawa.com

Product Design

Hawa Purolino Plus 80 consisting of running track (aluminum), panel, running gear with ball bearing rollers, suspension wedge, soft closing mechanism, track buffer, floor guide with zero clearance

Optional:

- (....) Profileset for fixed glazing
- (....) Floor / wall connection profile for fixed glazing
- (....) Wall mounting system end profile set
- (....) Wall mounting system wall profile set
- (....) Wall connection profile
- (....) Protective edge trim
- (....) Vertical sealing profile
- (....) Bottom door stopper
- (....) Toplock lock

Interfaces

Door leaf

- Glass processing for suspension wedge