

Fitting for top-running glass doors up to 400 kg (882 lbs.), with surface mounted running track. Ceiling mounting.

Product-Highlights



Security

ESG up to 16 mm (5/8") thick can be installed for greater stability of the doors, especially with large elements



Flexibility

With weights of up to 400 kg (882 lbs.) per element, even unusual building projects can be accomplished

Technical guidelines

Max. Door weight	400 kg (882 lbs.)
Door thickness	8–16 mm (5/16" to 5/8")
Max. Door height	3500 mm (11' 5 25/32")
Max. Door width	3000 mm (9' 10 1/8")
Max. opening width	12000 mm (39' 4 7/16")
Height adjustable	+/- 6 mm (1/4")
Soft close	No
Door material	Glass;Alu Glass Wood Mix;Metal
Finish color of visible profiles	Aluminum anodized;Aluminum raw

System options

Ceiling mounting	Yes
Top-running	Yes

Application area

Utilization medium / semi-public access	Yes
Utilization high / public access	Yes

Warranty

With the exception of parts subject to wear and tear, Hawa warrants the flawless functioning of the products delivered by it, as well as the durability of all parts, for a period of 2 years commencing from the transfer of risk.

Product Design

Hawa Shopfront G 400 consisting of running track (stainless steel), running track with steel roller ball bearing, suspension and glass retaining profile, top pivot bearing, bottom guide piece, floor guide profile.

Optional:

- (...) Bottom thrust bearing
- (...) Floor sleeve
- (...) Bar bolt lock

Interfaces

Door leaf

- Glass with processing VSG/ ESG
- Positive-fitting glass fixing with point fixing
- Top and bottom profile sealed in with silicone

Hawa Sliding Solutions AG

Untere Fischbachstrasse 4, 8932 Mettmenstetten, Switzerland
Phone +41 44 787 17 17, info@hawa.com, www.hawa.com