

**Fitting for top-running wooden doors up to 150 kg (330 lbs.), with surface mounted running track or running track flush with the ceiling. Ceiling mounting.**

### Product-Highlights



#### Aesthetics

Barely visible technology thanks to hardware components integrated in the doors



#### Comfort

Quiet running thanks to the running gear with plastic-coated precision ball bearings

### Technical guidelines

Max. Door weight	150 kg (330 lbs.)
Door thickness	35–80 mm (1 3/8" to 3 5/32")
Max. Door height	4000 mm (13'1 15/32")
Max. Door width	3000 mm (9' 10 1/8")
Max. Opening width	2950 mm (9' 8 5/32")
Height adjustable	+/- 5 mm (3/16")
Soft close	No
Door material	Wood
Finish color of visible profiles	Aluminum anodized

### System options

Ceiling mounting	Yes
Ceiling mounting recessed	Yes
Top-running	Yes

### Application area

Utilization light / semi-public access	Yes
Utilization medium / semi-public access	Yes

### Warranty

With the exception of parts subject to wear and tear, Hawa warrants the flawless functioning of the products delivered by it, as well as the durability of all parts, for a period of 2 years commencing from the transfer of risk.

### Product Design

Hawa Silenta 150 B consisting of running track (aluminum), running gear with 4 ball bearing rollers, suspension profile with suspension carriage, track buffer, floor guide with zero clearance

Optional:

- (...) Guide track, for groove mounting, bottom, plastic
- (...) Bottom door stopper, with centering part
- (...) Lightweight metal support profile (for better door weight distribution)
- (...) Guide track embedded in the floor

### Interfaces

#### Door leaf

- Cut-out for suspension profiles (H × W) 34 × 26 mm (1 11/32" × 1 1/32")
- Screw fixed support profiles
- Guide groove (H × W) 25 × 14 mm (31/32" × 9/16") (28 × 17 mm (1 3/32" × 21/32") with plastic guide track)

### Hawa Sliding Solutions AG

Untere Fischbachstrasse 4, 8932 Mettmenstetten, Switzerland  
Phone +41 44 787 17 17, info@hawa.com, www.hawa.com