



Fitting for top-running glass doors up to 250 kg (551 lbs.), with surface mounted running track. Wall or ceiling mounting.

Product-Highlights	Comfort High quality steel ball bearing with heavy weights		rollers for quiet, smooth running, even
	Security	Very safe thanks to positive-f	it glass fixing
Technical guidelines	Max. Door weight		250 kg (551 lbs.)
	Door thickness		35-80 mm (1 3/8" to 3 5/32")
	Max. Door height		4000 mm (13' 1 15/32'')
	Max. Door width		3000 mm (9' 10 1/8'')
	Max. Opening width Height adjustable Soft close Door material		2950 mm (9' 8 5/32'')
			+/- 6 mm (1/4'')
			No
			Alu Glass Wood Mix; Metal
	Finish color of visible profiles		Stainless steel
System options	Wall mounting		Yes
	Ceiling mounting		Yes
	Top-running		Yes
Application area	Utilization medium / semi-public access		Yes
	Utilization high / public access		Yes

Warranty With the exception of parts subject to wear and tear, Hawa warrants the flawless

functioning of the products delivered by it, as well as the durability of all parts, for a period

of 2 years commencing from the transfer of risk.

Product Design

Hawa Super 250 M consisting of running track (stainless steel, wall thickness 5.0 mm (3/16'')), 2-roller running gear with ball bearing rollers, track buffer, bottom guide.

Optional:

(.....) Bottom guide profile (.....) Bottom door stopper

Interfaces Door leaf

- Screw fixed support flange
- Guide groove (H \times W) 30 \times 13 mm (1 3/16" x 1/2")