

Fitting for top-running wooden doors up to 500 kg (1102 lbs.), with screwed on running track. Without soft and self closing system. Wall or ceiling mounting.

Product-Highlights

Flexibility

Steel suspension bracket for screw fixing or welding


Comfort

High quality steel ball bearing roller for quiet, smooth running, even with heavy weights

Technical guidelines

| | |
|----------------------------------|----------------------------------|
| Max. Door weight | 500 kg (1102 lbs.) |
| Door thickness | 45–100 mm (1 25/32" to 3 15/16") |
| Max. Door height | 6000 mm (19' 8 7/32") |
| Max. Door width | 5000 mm (16' 4 27/32") |
| Max. Opening width | 4950 mm (16' 2 7/8") |
| Height adjustable | +12 / -8 mm (+15/32" / -5/16") |
| Soft close | No |
| Door material | Wood |
| Finish color of visible profiles | Stainless steel |

System options

| | |
|------------------|-----|
| Wall mounting | Yes |
| Ceiling mounting | Yes |
| Top-running | Yes |

Application area

| | |
|---|-----|
| Utilization light / semi-public access | Yes |
| Utilization medium / semi-public access | Yes |
| Utilization high / public access | Yes |

Warranty

With the exception of parts subject to wear and tear, Hawa warrants the flawless functioning of the products delivered by it, as well as the durability of all parts, for a period of 2 years commencing from the transfer of risk.

Product Design

Hawa Super 500 A consisting of running track (stainless steel, wall thickness 5.0 mm (3/16")), bracket with suspension carriage and 3-roller ball bearing rollers, spring buffer, bottom guide.

Optional:
(.....) Track stopper for screw fixing

Interfaces
Door leaf

- Cut-out for bracket suspension
- Rear drill hole for spring buffer Ø 20 mm (25/32")/ depth 102 mm (4 1/32")
- Screw fixed bracket housing
- Guide groove (H × W) 40 × 6 mm (1 9/16" × 1/4")

Steel suspension

- for screw fixing or welding

Hawa Sliding Solutions AG

Untere Fischbachstrasse 4, 8932 Mettmenstetten, Switzerland
Phone +41 44 787 17 17, info@hawa.com, www.hawa.com