

**Frame profile for fitting for top-running glass doors up to 150 kg (330 lbs.), with surface mounted running track. Ceiling mounting. Fully opening.**

**Product-Highlights**



**Security**

The frame offers additional stability for tall doors



**Comfort**

The frame profile also seals and protects against drafts

**Technical guidelines**

Max. Door weight	150 kg (330 lbs.)
Door thickness	10–12.7 mm (13/32" to 1/2")
Max. Door height	3500 mm (11' 5 25/32")
Max. Door width	1500 mm (4' 11 1/16")
Max. Opening width	12000 mm (39' 4 7/16")
Height adjustable	+6 / -3 mm (+1/4" / -1/8")
Soft close	No
Door material	Alu Glass Wood Mix
Finish color of visible profiles	Aluminum anodized

**System options**

Ceiling mounting	Yes
Top-running	Yes

**Application area**

Utilization medium / semi-public access	Yes
Utilization high / public access	Yes

**Tests**

Building hardware – Hardware for sliding doors and folding doors according to EN 1527 / 2013  
 – Duration of functionality: Class 6 (highest class = 100,000 cycles)

Hardware for furniture – Roller fittings for sliding doors according to EN 15706 : 2008 – Level 3  
 – Overload test  
 – Functional test

**Warranty**

With the exception of parts subject to wear and tear, Hawa warrants the flawless functioning of the products delivered by it, as well as the durability of all parts, for a period of 2 years commencing from the transfer of risk.

**Product Design**

Hawa Variotec 150 GR - additional frame profiles for Hawa Variotec 150 GV

**Interfaces**

**Seal and wall connections**

– Centering of door elements and minimal sealing using sealing profiles

**Stacking area**

– Individual stacking area positioning possible

**Floor**

– Processing on floor for guide track or locks