

Fitting for 1 vertically sliding wooden window leaf up to 150 kg (330 lbs.), with lateral guide tracks and counterweight. Design Inslide. Half opening.

Product-Highlights



Comfort

No restriction to use of space, since the open window does not protrude into the room



Productivity

Low production cost, as the rebates of the frame timbers correspond to the standard

Technical guidelines

Max. shutter weight	150 kg (330 lbs.)
Shutter thickness	85 mm (3 11/32")
Max. shutter height	1200 mm (3' 11 1/4")
Max. shutter width	3200 mm (10' 5 31/32")

Application area

Utilization light / semi-public access	Yes
Utilization medium / semi-public access	Yes
Inland, more than 20 km from the coast	Yes
Coastal area, less than 20 km from the coast	Yes

Warranty

With the exception of parts subject to wear and tear, Hawa warrants the flawless functioning of the products delivered by it, as well as the durability of all parts, for a period of 2 years commencing from the transfer of risk.

Product Design

Hawa Vertical 150 consisting of guide tracks (plastic), guide brackets, pin lock, wire cable 4 mm (5/32"), rope support, pulley bracket, deflection rollers

Interfaces

Counterweight

– Customer-provided

Paneling

– Lining customer-provided
– Provide cavity at side and top for counterweight and deflection rollers